

Library

Argonne National Laboratory

MULTIGROUP CALCULATIONS OF
EFFECTIVE NEUTRON FRACTION β_{eff} ,
PROMPT NEUTRON LIFETIME ℓ_p ,
AND RELATED KINETICS
PARAMETERS FOR LARGE, FAST,
PLUTONIUM-FUELED REACTORS

by

H. A. Sandmeier

PROPERTY OF
ARGONNE NATIONAL LAB.
IDAHO LIBRARY

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:

- A. Makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or*
- B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.*

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission, or employee of such contractor, to the extent that such employee or contractor of the Commission, or employee of such contractor prepares, disseminates, or provides access to, any information pursuant to his employment or contract with the Commission, or his employment with such contractor.

ARGONNE NATIONAL LABORATORY
9700 South Cass Avenue
Argonne, Illinois

MULTIGROUP CALCULATIONS OF EFFECTIVE NEUTRON
FRACTION β_{eff} , PROMPT NEUTRON LIFETIME ℓ_p , AND
RELATED KINETICS PARAMETERS FOR LARGE, FAST,
PLUTONIUM-FUELED REACTORS

by

H. A. Sandmeier

Reactor Engineering Division

September 1961

Operated by The University of Chicago
under
Contract W-31-109-eng-38

TABLE OF CONTENTS

	<u>Page</u>
ABSTRACT	4
INTRODUCTION.	4
KINETICS PARAMETERS TO BE EVALUATED.	5
PROMPT NEUTRON LIFETIME, ℓ_p	6
ENERGY SPECTRUM FOR LARGE FAST REACTORS.	7
WORTH FUNCTIONS.	7
FUNDAMENTAL DELAYED-NEUTRON DATA.	8
NUMERICAL EVALUATION FOR REPRESENTATIVE LARGE FAST REACTOR CORES	9
ZERO-POWER TRANSFER FUNCTION $ZP(j\omega)$	11
CONCLUSIONS.	20
ACKNOWLEDGEMENT	21
REFERENCES.	22

LIST OF TABLES

No.	Title	Page
I.	Fundamental Delayed-neutron Data	10
II.	Effective Delayed-neutron Fraction β_{eff} and Related Kinetics Data for 800-liter, Plutonium A Metal, Oxide, and Carbide Fast Reactor Cores.	12
III.	Effective Delayed-neutron Fraction β_{eff} and Related Kinetics Data for 1500-liter, Plutonium A Metal, Oxide, and Carbide Fast Reactor Cores.	13
IV.	Effective Delayed-neutron Fraction β_{eff} and Related Kinetics Data for 1500-liter, Plutonium B Metal, Oxide, and Carbide Fast Reactor Cores.	14
V.	Effective Delayed-neutron Fraction β_{eff} and Related Kinetics Data for 1500-liter, Plutonium C Metal, Oxide, and Carbide Fast Reactor Cores.	15
VI.	Effective Delayed-neutron Fraction β_{eff} and Related Kinetics Data for 2500-liter, Plutonium A Metal, Oxide, and Carbide Fast Reactor Cores.	16

LIST OF FIGURES

No.	Title	Page
I.	Comparison of Spectra Calculated from 1500-liter Metal, Oxide and Carbide, Plutonium (Type C) Fueled Fast Reactors .	8
II.	Zero Power Transfer Function Amplitude $ ZP(j\omega) $ for Large Plutonium (Type A and C) Oxide, Carbide and Metal Fueled Fast Reactors	17
III.	Zero Power Transfer Function Amplitude $ ZP(j\omega) $ for Large Plutonium (Type A and B) Oxide, Carbide and Metal Fueled Fast Reactors	18
IV.	Zero Power Transfer Function Phase Angle $\angle ZP(j\omega)$ for Large Plutonium (Type A, B and C) Oxide, Carbide and Metal Fueled Fast Reactors. (800 L, 1500 L and 2500 L Cores)	19
V.	Load Power Transfer Function for Fast Plutonium and U^{235} Reactor	20

MULTIGROUP CALCULATIONS OF EFFECTIVE NEUTRON FRACTION β_{eff} , PROMPT NEUTRON LIFETIME ℓ_p , AND RELATED KINETICS PARAMETERS FOR LARGE, FAST, PLUTONIUM-FUELED REACTORS

by

H. A. Sandmeier

ABSTRACT

Large, plutonium-fueled, fast reactors will have a different kinetic behavior than fast reactors fueled with U^{235} , due to the much smaller delayed-neutron fraction emitted in the fissioning of plutonium.

The fissioning of Pu^{240} , Pu^{241} , Pu^{242} , and especially U^{238} , which emit more delayed neutrons per fission than Pu^{239} , introduces a considerable increase in β_{eff} over that for a hypothetical pure Pu^{239} reactor.

The cases considered are 800-, 1500- and 2500-liter cores fueled with plutonium of different isotopic content, which lead to effective delayed-neutron fractions of approximately one-half the values of similar U^{235} - U^{238} -fueled fast reactors. The energy spectrum and the number of fissions weighted with their importance are recorded in order to reason physically on the obtained parameters.

INTRODUCTION

Due to the increased interest in large, plutonium-fueled, fast reactors, we obtained some important physics quantities related to the kinetics behavior and stability of such systems.

The prompt neutron lifetime ℓ_p and the effective delayed neutron fraction β_{eff} have been evaluated by using a machine program⁽¹⁾ which utilized as input the space and energy-dependent real and adjoint flux for multigroup solutions in spherical geometry. In order to be able to reason physically on the obtained parametric values, the total number of fissions for each Pu isotope, as well as for U^{238} , has been evaluated for all cores. Expressions proportional to the worth of prompt and delayed neutrons were obtained. All worth ratio functions are related to the worth of a prompt Pu^{239} neutron in the core. Finally, six β_{eff} values are obtained for each

delayed neutron precursor family. By using BUM,⁽²⁾ the transfer function code, one gets the zero-power transfer function $ZP(j\omega)$. The cores used as representative examples were the ones reported by Yiftah and Okrent.⁽³⁾ For the 1500-liter cores, the effect on the above parameters due to different Pu isotopes, i.e., Pu^{239} , Pu^{240} , Pu^{241} , and Pu^{242} , have been calculated, as well as the variations due to use of Pu metal, Pu oxide or Pu carbide fuels. The effect of core size was studied by considering 800-, 1500-, and 2500-liter, pure Pu^{239} metal, oxide, and carbide cores. The diluent in all cores, as well as the fertile material in the blanket, was U^{238} .

KINETICS PARAMETERS TO BE EVALUATED

The formula used to obtain β_{eff} , ℓ_p , and worth functions follows essentially the basic definitions given in the papers by Long et al.,⁽⁴⁾ and by Meneghetti⁽⁵⁾:

$$\beta_{eff} = \frac{\sum_{\text{Fiss.mat.m}} \left\{ \beta^m \int \left(\sum_{i=1}^{16} (\nu \Sigma_f)_i^m \phi_i \right) \left(\sum_{j=1}^{16} \beta_{dj}^m \phi_j^* \right) dV \right\}}{\sum_{\text{Fiss.mat.m}} \left\{ \beta^m \int \left(\sum_{i=1}^{16} (\nu \Sigma_f)_i^m \phi_i \right) \left(\sum_{j=1}^{16} \beta_{dj}^m \phi_j^* \right) dV + (1 - \beta^m) \int \left(\sum_{i=1}^{16} (\nu \Sigma_f)_i^m \phi_i \right) \left(\sum_{j=1}^{16} \chi_j^m \phi_j^* \right) dV \right\}} \quad (1)$$

The first factor under the integral sign in the numerator of Eq. (1)

$$\sum_{i=1}^{16} (\nu \Sigma_f)_i^m \phi_i \quad (2)$$

is proportional to the number of fission neutrons born in all groups. In order to get the number of delayed neutrons, we multiply the sum (2) by β^m , the delayed neutron fraction for material m, where

$$\beta^m = \left(\frac{n}{F} \right)^m / \bar{\nu}^m \quad (3)$$

It is important to remember that β^m is obtained from two measured quantities, the total number of delayed neutrons per fission, $(n/F)^m$, for material m, and the total neutrons released per fission, $\bar{\nu}^m$, for material m. Both quantities are energy dependent, and it is advisable to state the reference for both values if numerical values for delayed neutron fractions are quoted.

The second factor under the integral sign in the numerator of Eq. (1),

$$\sum_{j=1}^{16} \beta_{dj}^m \phi_j^* \quad (4)$$

where

$$\sum_{j=1}^{16} \beta_{dj}^m = 1 \quad ,$$

represents a feeding of the delayed neutrons with energies varying in the range from 200 to 500 kv into the proper energy group in the multigroup representation. Furthermore we have to take into account the importance ϕ_j^* of a neutron in this group.

In these calculations, both the real and adjoint flux are normalized, but since all quantities in this paper are ratios of ϕ and ϕ^* , we don't have to be concerned with this factor. The numerical value of Eq. (2) after integration over all regions and fissionable materials represents, therefore, a normalized number of fission neutrons. Finally, we integrate the numerator of Eq. (1) over all regions where fission takes place and sum over all fissionable materials.

In the denominator we sum up all the delayed and prompt neutrons born in all regions for all fissionable materials. The quantity χ_j^m separates the prompt fission neutrons born into the individual energy groups, and then we attach the proper importance to them expressed by ϕ_j^* , the adjoint flux.

For kinetics studies we must obtain the individual $\beta_{eff(n)}$ for the usual six families of precursors:

$$\beta_{eff(n)} = \frac{\sum_{\text{Fiss.mat.m}} \left\{ \beta_{(n)}^m \int \left(\sum_{i=1}^{16} (\nu \Sigma_f)_i^m \phi_i \right) \left(\sum_{j=1}^{16} \beta_{dj}^m \phi_j^* \right) dV \right\}}{\sum_{\text{Fiss.mat.m}} \left\{ \beta^m \int \left(\sum_{i=1}^{16} (\nu \Sigma_f)_i^m \phi_i \right) \left(\sum_{j=1}^{16} \beta_{dj}^m \phi_j^* \right) dV + (1 - \beta^m) \int \left(\sum_{i=1}^{16} (\nu \Sigma_f)_i^m \phi_i \right) \left(\sum_{j=1}^{16} \chi_j^m \phi_j^* \right) dV \right\}} \quad (5)$$

The only difference between Eq. (5) and Eq. (1) is that in the numerator we insert for the delayed neutron fraction $\beta_{(n)}^m$ the delayed neutron fraction for the precursor family n for each fissionable material m .

PROMPT NEUTRON LIFETIME ℓ_p

The formula for the prompt neutron lifetime in multigroup notation is

$$\ell_p = \frac{\int \left(\sum_{i=1}^{16} \frac{\phi_i \phi_j^*}{v_i} \right) dV}{\sum_{\text{Fiss.Mat.m}} \int \left(\sum_{i=1}^{16} (\nu \Sigma_f)_i^m \phi_i \right) \left(\sum_{j=1}^{16} \chi_j^m \phi_j^* \right) dV} \quad (6)$$

where v_i is the average speed of a neutron in a group:

$$\left(\frac{1}{v_i}\right) = \frac{\int_{E_L}^{E_H} \frac{1}{v(E)} \phi \phi^* dE}{\int_{E_L}^{E_H} \phi \phi^* dE} \quad (7)$$

The above quantity was evaluated in two ways. First, it was assumed that both real and adjoint flux are the same (one-group perturbation theory); then the spectrum was assumed to be proportional to $1/E$, as one gets in a medium with pure scattering without absorption. Secondly, a 574-energy-group solution by Hummel⁽⁶⁾ for an 800-liter plutonium (TYPE A) oxide core was used to evaluate average neutron speeds in the 16-group set of YOM.⁽⁷⁾ The numerical variations on the prompt neutron lifetime by both methods were found to be insignificant.

ENERGY SPECTRUM FOR LARGE FAST REACTORS

As a representative illustration we show in Fig. 1 the spectrum of a 1500-liter Pu (TYPE C) metal, oxide, and carbide-fueled fast reactor. The adjoint flux for the oxide case is also shown.

WORTH FUNCTIONS

The evaluated worth functions for delayed and prompt neutrons are

$$W_d^m = \frac{\int \left(\sum_{i=1}^{16} (\nu \Sigma_f)_i^m \phi_i \right) \left(\sum_{j=1}^{16} \beta_{dj}^m \phi_j^* \right) dV}{\int \left(\sum_{i=1}^{16} (\nu \Sigma_f)_i^m \phi_i \right) dV} \quad (8)$$

and

$$W_p^m = \frac{\int \left(\sum_{i=1}^{16} (\nu \Sigma_f)_i^m \phi_i \right) \left(\sum_{j=1}^{16} \chi_j^m \phi_j^* \right) dV}{\int \left(\sum_{i=1}^{16} (\nu \Sigma_f)_i^m \phi_i \right) dV} \quad (9)$$




Fig. 1

COMPARISON OF SPECTRA CALCULATED FROM 1500-LITER METAL, OXIDE AND CARBIDE, PLUTONIUM (TYPE C) FUELED FAST REACTORS

FUNDAMENTAL DELAYED-NEUTRON DATA

The latest available delayed-neutron data for Pu^{239} , Pu^{240} , and Pu^{241} was taken from Cox,⁽⁸⁾ for Pu^{242} from Smith,⁽⁹⁾ and for U^{238} from ANL-5800.⁽¹⁰⁾

The delayed-neutron spectrum was assumed to be the same for all fissionable materials, i.e., χ_j^m is the same for all fissionable materials considered. Keepin⁽¹¹⁾ discusses the delayed-neutron energies for the 54-, 22-, 5.9-, 2.2-, 0.46-, and 0.13-sec half-life precursors of U^{235} . Stehney⁽¹²⁾ suggests that it is reasonable to assume that the delayed-neutron spectrum for the Pu isotopes is the same as for U^{235} . This suggests that the same precursors are responsible for the delayed neutrons in either case, U^{235} or the Pu isotopes. For all Pu isotopes the delayed neutrons from the 55-sec half-life precursor have a mean energy of approximately 250 kv and are therefore fed into energy group 7 in YOM.⁽⁷⁾ The five other groups with energies ranging from 300 to 500 kv are given off into YOM⁽⁷⁾ energy group 6.

All numerical values used for Pu^{239} , Pu^{240} , Pu^{241} , Pu^{242} , and U^{238} are listed in Table I.

NUMERICAL EVALUATION FOR REPRESENTATIVE LARGE FAST REACTOR CORES

The cores investigated numerically are taken from Yiftah and Okrent.⁽³⁾ For clarity of presentation we repeat here the pertinent data for the fuel and the plutonium compositions, as well as the geometrical dimensions of the reactors investigated.

Core Volume:

800, 1500, and 2500 liters

(Where necessary, some additional core volumes were used.)

Core Volume Fractions:

Fuel and Fertile Material	0.25
Structural Material	0.25
Coolant	0.5

Fuels:

	Density, g/cc
$Pu-U^{238}$	19.0
PuO_2-UO_2	8.4
$PuC-UC$	11.39

Plutonium Composition:

	Atom Per Cent			
TYPE	Pu^{239}	Pu^{240}	Pu^{241}	Pu^{242}
A	100.0	0	0	0
B	74.7	10.2	12.4	2.7
C	40.0	10.0	25.0	25.0

TABLE I
FUNDAMENTAL DELAYED-NEUTRON DATA

FISSIONABLE MATERIAL	λ ()	β ()	
Pu^{239}	(1) 0.0127690 (2) 0.0300846 (3) 0.1237760 (4) 0.3254225 (5) 1.1216010 (6) 2.6970817	(1) 0.00007241 (2) 0.00062759 (3) 0.00044483 (4) 0.00068621 (5) 0.00017931 (6) 0.00009310	$\beta_{d6} = 0.96557700$ $\beta_{d7} = 0.03442440$ $\beta = 0.00210345$ $\nu = 2.9$ REF. (8)
Pu^{240}	(1) 0.0129415 (2) 0.0313076 (3) 0.1348540 (4) 0.3332452 (5) 1.3564570 (6) 4.0299400	(1) 0.00006666 (2) 0.00072121 (3) 0.00049090 (4) 0.00095454 (5) 0.00036061 (6) 0.00007273	$\beta_{d6} = 0.97502430$ $\beta_{d7} = 0.02499800$ $\beta = 0.00266660$ $\nu = 3.3$ REF. (8)
Pu^{241}	(1) 0.0128000 (2) 0.0299000 (3) 0.1238000 (4) 0.3519000 (5) 1.6120000 (6) 4.6210000	(1) 0.00005168 (2) 0.00122483 (3) 0.00092282 (4) 0.00208050 (5) 0.00097315 (6) 0.00008389	$\beta_{d6} = 0.99031600$ $\beta_{d7} = 0.00968305$ $\beta = 0.00533685$ $\nu = 2.98$ REF. (8)
Pu^{242}	(1) 0.0128360 (2) 0.0315060 (3) 0.1155250 (4) 0.3465750 (5) 1.3863000 (6) 3.4657500	(1) 0.00003030 (2) 0.00163636 (3) 0.00106060 (4) 0.00333330 (5) 0.00181818 (6) 0.00012121	$\beta_{d6} = 0.96212100$ $\beta_{d7} = 0.03787800$ $\beta = 0.00799995$ $\nu = 3.3$ REF. (9)
U^{238}	(1) 0.0132000 (2) 0.0321000 (3) 0.1390000 (4) 0.3580000 (5) 1.4100000 (6) 4.0200000	(1) 0.00020400 (2) 0.00215100 (3) 0.00254300 (4) 0.00609200 (5) 0.00353300 (6) 0.00117800	$\beta_{d6} = 0.98707000$ $\beta_{d7} = 0.01299000$ $\beta = 0.01570000$ $\nu = 2.62$ REF. (10)

Coolant:

Liquid Sodium 0.84 g/cc

Structural Material:

Stainless Steel

Blanket Thickness:

45 cm (uranium)

Blanket Volume Fractions:U²³⁸ 0.6

Na 0.2

Fe 0.2

Reflector Thickness:

30 cm

Reflector Volume Fractions:

Fe 0.6

Na 0.4

The effect of different fuels was investigated by considering 1500-liter cores with different plutonium compositions: TYPE A, B, and C for all three fuels, i.e., Pu-U²³⁸, PuO₂-UO₂ and PuC-UC in the core.

The effect of varying core volume was shown by considering 800-, 1500-, and 2500-liter cores with plutonium TYPE A; Pu-U²³⁸, PuO₂-UO₂ and PuC-UC fuels.

The numerical values are shown in Tables II through VI.

ZERO-POWER TRANSFER FUNCTION $ZP(j\omega)$

For kinetics studies it is of interest to obtain the zero-power transfer function. Argonne code BUM⁽²⁾ was used for this purpose. The data necessary to evaluate $ZP(j\omega)$ ⁽¹³⁾ are the effective delayed neutron fractions, $\beta_{eff(1)} \dots \beta_{eff(6)}$, and the neutron lifetime ℓ_p , listed in Tables II through VI.

The decay constants λ used for all transfer functions are the values for Pu²³⁹ listed in Table I. The effect of using different decay constants was investigated and found to be negligible.

The values for $ZP(j\omega)$ in amplitude and phase are shown in Figs. II through IV. As a comparison we show a previously obtained zero-power transfer function $ZP(j\omega)$ for EBR-I, Mark III, calculated by Okrent.⁽¹⁴⁾

TABLE II

EFFECTIVE DELAYED-NEUTRON FRACTION β_{eff} AND RELATED KINETICS DATA FOR 800-LITER, PLUTONIUM A METAL, OXIDE, AND CARBIDE FAST REACTOR CORES

$\beta_{\text{eff}} ()$	$W_d ()$ WORTH OF DELAYED NEUTRONS IN CORE (c) AND BLANKET (b) FOR FISSIONABLE MATERIALS	$W_p ()$ WORTH OF PROMPT NEUTRONS IN CORE (c) AND BLANKET (b) FOR FISSIONABLE MATERIALS	$\frac{FIS()}{FIS(\text{tot})}$	WORTH RATIOS
--------------------------	---	--	----------------------------------	--------------

CORE: 800 LITER, PLUTONIUM A, METAL; $\ell_p = 1.66752 \times 10^{-7}$; $\beta_{\text{eff}} = 0.00390187$

(1) 0.00008187	(c, U ²³⁸) = 0.962	(c, U ²³⁸) = 1.130	(c, tot) = 0.940	$\left[\frac{W_d(c, U^{238})}{W_p(c, Pu^{239})} \right] = 0.969$
(2) 0.00076924	(c, Pu ²³⁹) = 0.939	(c, Pu ²³⁹) = 1.106	(b, tot) = 0.060	
(3) 0.00070395	_____	_____	(c, U ²³⁸) = 0.161	
(4) 0.00142400	_____	_____	(c, Pu ²³⁹) = 0.779	$\left[\frac{W_d(c, Pu^{239})}{W_p(c, Pu^{239})} \right] = 0.949$
(5) 0.00067463	_____	_____	_____	
(6) 0.00024798	(b, U ²³⁸) = 0.288	(b, U ²³⁸) = 0.387	(b, U ²³⁸) = 0.060	$\left[\frac{W_p(c, U^{238})}{W_p(c, Pu^{239})} \right] = 1.022$

CORE: 800 LITER, PLUTONIUM A, OXIDE; $\ell_p = 3.00751 \times 10^{-7}$; $\beta_{\text{eff}} = 0.00321875$

(1) 0.00007893	(c, U ²³⁸) = 1.025	(c, U ²³⁸) = 1.109	(c, tot) = 0.916	$\left[\frac{W_d(c, U^{238})}{W_p(c, Pu^{239})} \right] = 0.945$
(2) 0.00072036	(c, Pu ²³⁹) = 1.001	(c, Pu ²³⁹) = 1.085	(b, tot) = 0.084	
(3) 0.00060705	_____	_____	(c, U ²³⁸) = 0.071	
(4) 0.00114192	_____	_____	(c, Pu ²³⁹) = 0.844	$\left[\frac{W_d(c, Pu^{239})}{W_p(c, Pu^{239})} \right] = 0.922$
(5) 0.00048226	_____	_____	_____	
(6) 0.00018922	(b, U ²³⁸) = 0.341	(b, U ²³⁸) = 0.434	(b, U ²³⁸) = 0.084	$\left[\frac{W_p(c, U^{238})}{W_p(c, Pu^{239})} \right] = 1.022$

CORE: 800 LITER, PLUTONIUM A, CARBIDE; $\ell_p = 2.50021 \times 10^{-7}$; $\beta_{\text{eff}} = 0.00348409$

(1) 0.00008021	(c, U ²³⁸) = 1.001	(c, U ²³⁸) = 1.114	(c, tot) = 0.924	$\left[\frac{W_d(c, U^{238})}{W_p(c, Pu^{239})} \right] = 0.918$
(2) 0.00074041	(c, Pu ²³⁹) = 0.978	(c, Pu ²³⁹) = 1.091	(b, tot) = 0.076	
(3) 0.00064502	_____	_____	(c, U ²³⁸) = 0.103	
(4) 0.00125111	_____	_____	(c, Pu ²³⁹) = 0.821	$\left[\frac{W_d(c, Pu^{239})}{W_p(c, Pu^{239})} \right] = 0.896$
(5) 0.00055609	_____	_____	_____	
(6) 0.00021124	(b, U ²³⁸) = 0.322	(b, U ²³⁸) = 0.420	(b, U ²³⁸) = 0.076	$\left[\frac{W_p(c, U^{238})}{W_p(c, Pu^{239})} \right] = 1.021$

TABLE III

EFFECTIVE DELAYED-NEUTRON FRACTION β_{eff} AND RELATED KINETICS DATA FOR 1500-LITER, PLUTONIUM A METAL, OXIDE, AND CARBIDE FAST REACTOR CORES

$\beta_{\text{eff}} ()$	$W_d ()$ WORTH OF DELAYED NEUTRONS IN CORE (c) AND BLANKET (b) FOR FISSIONABLE MATERIALS	$W_p ()$ WORTH OF PROMPT NEUTRONS IN CORE (c) AND BLANKET (b) FOR FISSIONABLE MATERIALS	$\frac{FIS()}{FIS(\text{tot})}$	WORTH RATIOS
--------------------------	---	--	----------------------------------	--------------

CORE: 1500 LITER, PLUTONIUM A, METAL; $\ell_p = 1.89851 \times 10^{-7}$; $\beta_{\text{eff}} = 0.00390760$

(1) 0.00008131	(c, U^{238}) = 0.973	(c, U^{238}) = 1.161	(c, tot) = 0.955	$\left[\frac{W_d(c, U^{238})}{W_p(c, Pu^{239})} \right] = 0.854$
(2) 0.00076528	(c, Pu^{239}) = 0.952	(c, Pu^{239}) = 1.139	(b, tot) = 0.045	
(3) 0.00070345	_____	_____	(c, U^{238}) = 0.174	
(4) 0.00142813	_____	_____	(c, Pu^{239}) = 0.781	$\left[\frac{W_d(c, Pu^{239})}{W_p(c, Pu^{239})} \right] = 0.836$
(5) 0.00068010	_____	_____	_____	
(6) 0.00024934	(b, U^{238}) = 0.258	(b, U^{238}) = 0.352	(b, U^{238}) = 0.045	$\left[\frac{W_p(c, U^{238})}{W_p(c, Pu^{239})} \right] = 1.020$

CORE: 1500 LITER, PLUTONIUM A, OXIDE; $\ell_p = 3.78915 \times 10^{-7}$; $\beta_{\text{eff}} = 0.00320268$

(1) 0.00007830	(c, U^{238}) = 1.040	(c, U^{238}) = 1.138	(c, tot) = 0.935	$\left[\frac{W_d(c, U^{238})}{W_p(c, Pu^{239})} \right] = 0.932$
(2) 0.00071507	(c, Pu^{239}) = 1.017	(c, Pu^{239}) = 1.116	(b, tot) = 0.065	
(3) 0.00060362	_____	_____	(c, U^{238}) = 0.082	
(4) 0.00113731	_____	_____	(c, Pu^{239}) = 0.853	$\left[\frac{W_d(c, Pu^{239})}{W_p(c, Pu^{239})} \right] = 0.911$
(5) 0.00048167	_____	_____	_____	
(6) 0.00018771	(b, U^{238}) = 0.309	(b, U^{238}) = 0.399	(c, U^{238}) = 0.065	$\left[\frac{W_p(c, U^{238})}{W_p(c, Pu^{239})} \right] = 1.020$

CORE: 1500 LITER, PLUTONIUM A, CARBIDE; $\ell_p = 2.99667 \times 10^{-7}$; $\beta_{\text{eff}} = 0.00347546$

(1) 0.00007951	(c, U^{238}) = 1.013	(c, U^{238}) = 1.144	(c, tot) = 0.942	$\left[\frac{W_d(c, U^{238})}{W_p(c, Pu^{239})} \right] = 0.903$
(2) 0.00073479	(c, Pu^{239}) = 0.991	(c, Pu^{239}) = 1.122	(b, tot) = 0.058	
(3) 0.00064226	_____	_____	(c, U^{238}) = 0.116	
(4) 0.00124947	_____	_____	(c, Pu^{239}) = 0.826	$\left[\frac{W_d(c, Pu^{239})}{W_p(c, Pu^{239})} \right] = 0.883$
(5) 0.00055799	_____	_____	_____	
(6) 0.00021144	(c, U^{238}) = 0.289	(b, U^{238}) = 0.385	(b, U^{238}) = 0.058	$\left[\frac{W_p(c, U^{238})}{W_p(c, Pu^{239})} \right] = 1.020$

TABLE IV

EFFECTIVE DELAYED-NEUTRON FRACTION β_{eff} AND RELATED KINETICS DATA FOR 1500-LITER, PLUTONIUM B METAL, OXIDE, AND CARBIDE FAST REACTOR CORES

$\beta_{\text{eff}} ()$	$W_d ()$ WORTH OF DELAYED NEUTRONS IN CORE (c) AND BLANKET (b) FOR FISSIONABLE MATERIALS	$W_p ()$ WORTH OF PROMPT NEUTRONS IN CORE (c) AND BLANKET (b) FOR FISSIONABLE MATERIALS	$\frac{FIS()}{FIS(\text{tot})}$	WORTH RATIOS
--------------------------	---	--	----------------------------------	--------------

CORE: 1500 LITER, PLUTONIUM B, METAL; $\ell_p = 1.94110 \times 10^{-7}$; $\beta_{\text{eff}} = 0.00426902$

(1) 0.00007773	(c, U ²³⁸) = 0.963	(c, U ²³⁸) = 1.161	(c, tot) = 0.955	$\frac{W_d(c, U^{238})}{W_p(c, Pu^{239})} = 0.846$
(2) 0.00083204	(c, Pu ²³⁹) = 0.943	(c, Pu ²³⁹) = 1.139	(b, tot) = 0.045	
(3) 0.00075384	(c, Pu ²⁴⁰) = 0.957	(c, Pu ²⁴⁰) = 1.155	(c, U ²³⁸) = 0.174	
(4) 0.00158773	(c, Pu ²⁴¹) = 0.941	(c, Pu ²⁴¹) = 1.136	(c, Pu ²³⁹) = 0.625	$\frac{W_d(c, Pu^{239})}{W_p(c, Pu^{239})} = 0.828$
(5) 0.00077303	(c, Pu ²⁴²) = 0.956	(c, Pu ²⁴²) = 1.154	(c, Pu ²⁴⁰) = 0.018	
(6) 0.00024465	(b, U ²³⁸) = 0.257	(b, U ²³⁸) = 0.352	(c, Pu ²⁴¹) = 0.133	
			(c, Pu ²⁴²) = 0.005	
			(b, U ²³⁸) = 0.045	$\frac{W_p(c, U^{238})}{W_p(c, Pu^{239})} = 1.020$

CORE: 1500 LITER, PLUTONIUM B, OXIDE; $\ell_p = 3.88897 \times 10^{-7}$; $\beta_{\text{eff}} = 0.00369389$

(1) 0.00007436	(c, U ²³⁸) = 1.033	(c, U ²³⁸) = 1.138	(c, tot) = 0.934	$\frac{W_d(c, U^{238})}{W_p(c, Pu^{239})} = 0.926$
(2) 0.00080521	(c, Pu ²³⁹) = 1.011	(c, Pu ²³⁹) = 1.116	(b, tot) = 0.066	
(3) 0.00067342	(c, Pu ²⁴⁰) = 1.026	(c, Pu ²⁴⁰) = 1.131	(c, U ²³⁸) = 0.082	
(4) 0.00135141	(c, Pu ²⁴¹) = 1.010	(c, Pu ²⁴¹) = 1.114	(c, Pu ²³⁹) = 0.676	$\frac{W_d(c, Pu^{239})}{W_p(c, Pu^{239})} = 0.906$
(5) 0.00060539	(c, Pu ²⁴²) = 1.026	(c, Pu ²⁴²) = 1.131	(c, Pu ²⁴⁰) = 0.017	
(6) 0.00018410	(b, U ²³⁸) = 0.308	(b, U ²³⁸) = 0.400	(c, Pu ²⁴¹) = 0.155	
			(c, Pu ²⁴²) = 0.004	
			(b, U ²³⁸) = 0.066	$\frac{W_p(c, U^{238})}{W_p(c, Pu^{239})} = 1.020$

CORE: 1500 LITER, PLUTONIUM B, CARBIDE; $\ell_p = 3.07530 \times 10^{-7}$; $\beta_{\text{eff}} = 0.00392487$

(1) 0.00007574	(c, U ²³⁸) = 1.006	(c, U ²³⁸) = 1.144	(c, tot) = 0.942	$\frac{W_d(c, U^{238})}{W_p(c, Pu^{239})} = 0.896$
(2) 0.00081750	(c, Pu ²³⁹) = 0.985	(c, Pu ²³⁹) = 1.122	(b, tot) = 0.058	
(3) 0.00070596	(c, Pu ²⁴⁰) = 0.999	(c, Pu ²⁴⁰) = 1.137	(c, U ²³⁸) = 0.115	
(4) 0.00144617	(c, Pu ²⁴¹) = 0.984	(c, Pu ²⁴¹) = 1.121	(c, Pu ²³⁹) = 0.656	$\frac{W_d(c, Pu^{239})}{W_p(c, Pu^{239})} = 0.877$
(5) 0.00067184	(c, Pu ²⁴²) = 0.998	(c, Pu ²⁴²) = 1.137	(c, Pu ²⁴⁰) = 0.017	
(6) 0.00020766	(b, U ²³⁸) = 0.289	(b, U ²³⁸) = 0.395	(c, U ²³⁸) = 0.148	
			(c, Pu ²⁴²) = 0.005	
			(b, U ²³⁸) = 0.058	$\frac{W_p(c, U^{238})}{W_p(c, Pu^{239})} = 1.020$

TABLE V

EFFECTIVE DELAYED-NEUTRON FRACTION β_{eff} AND RELATED KINETICS DATA FOR 1500-LITER, PLUTONIUM C METAL, OXIDE, AND CARBIDE FAST REACTOR CORES

$\beta_{\text{eff}} ()$	$W_d ()$ WORTH OF DELAYED NEUTRONS IN CORE (c) AND BLANKET (b) FOR FISSIONABLE MATERIALS	$W_p ()$ WORTH OF PROMPT NEUTRONS IN CORE (c) AND BLANKET (b) FOR FISSIONABLE MATERIALS	$\frac{FIS()}{FIS(\text{tot})}$	WORTH RATIOS
--------------------------	---	--	----------------------------------	--------------

CORE: 1500 LITER, PLUTONIUM C, METAL; $\beta_p = 1.96703 \times 10^{-7}$; $\beta_{\text{eff}} = 0.00486485$

(1) 0.00007039	(c, U ²³⁸) = 0.937	(c, U ²³⁸) = 1.162	(c, tot) = 0.954	$\left[\frac{W_d(c, U^{238})}{W_p(c, Pu^{239})} \right] = 0.823$
(2) 0.00094009	(c, Pu ²³⁹) = 0.918	(c, Pu ²³⁹) = 1.139	(b, tot) = 0.046	
(3) 0.00082769	(c, Pu ²⁴⁰) = 0.931	(c, Pu ²⁴⁰) = 1.155	(c, U ²³⁸) = 0.173	
(4) 0.00185693	(c, Pu ²⁴¹) = 0.916	(c, Pu ²⁴¹) = 1.136	(c, Pu ²³⁹) = 0.395	$\left[\frac{W_d(c, Pu^{239})}{W_p(c, Pu^{239})} \right] = 0.806$
(5) 0.00093462	(c, Pu ²⁴²) = 0.931	(c, Pu ²⁴²) = 1.155	(c, Pu ²⁴⁰) = 0.020	
(6) 0.00023514	(b, U ²³⁸) = 0.252	(b, U ²³⁸) = 0.351	(c, Pu ²⁴¹) = 0.316	$\left[\frac{W_p(c, Pu^{239})}{W_p(c, Pu^{239})} \right] = 1.020$
			(c, Pu ²⁴²) = 0.050	
			(b, U ²³⁸) = 0.046	

CORE: 1500 LITER, PLUTONIUM C, OXIDE; $\beta_p = 3.95275 \times 10^{-7}$; $\beta_{\text{eff}} = 0.00447424$

(1) 0.00006663	(c, U ²³⁸) = 1.013	(c, U ²³⁸) = 1.139	(c, tot) = 0.934	$\left[\frac{W_d(c, U^{238})}{W_p(c, Pu^{239})} \right] = 0.908$
(2) 0.00094628	(c, Pu ²³⁹) = 0.991	(c, Pu ²³⁹) = 1.116	(b, tot) = 0.066	
(3) 0.00077465	(c, Pu ²⁴⁰) = 1.006	(c, Pu ²⁴⁰) = 1.132	(c, U ²³⁸) = 0.079	
(4) 0.00169958	(c, Pu ²⁴¹) = 0.990	(c, Pu ²⁴¹) = 1.114	(c, Pu ²³⁹) = 0.423	$\left[\frac{W_d(c, Pu^{239})}{W_p(c, Pu^{239})} \right] = 0.888$
(5) 0.00081130	(c, Pu ²⁴²) = 1.006	(c, Pu ²⁴²) = 1.131	(c, Pu ²⁴⁰) = 0.019	
(6) 0.00017678	(b, U ²³⁸) = 0.304	(b, U ²³⁸) = 0.398	(c, Pu ²⁴¹) = 0.364	$\left[\frac{W_p(c, U^{238})}{W_p(c, Pu^{239})} \right] = 1.021$
			(c, Pu ²⁴²) = 0.047	
			(b, U ²³⁸) = 0.066	

CORE: 1500 LITER, PLUTONIUM C, CARBIDE; $\beta_p = 3.12706 \times 10^{-7}$; $\beta_{\text{eff}} = 0.00464446$

(1) 0.00006822	(c, U ²³⁸) = 0.985	(c, U ²³⁸) = 1.145	(c, tot) = 0.941	$\left[\frac{W_d(c, U^{238})}{W_p(c, Pu^{239})} \right] = 0.877$
(2) 0.00094771	(c, Pu ²³⁹) = 0.964	(c, Pu ²³⁹) = 1.122	(b, tot) = 0.059	
(3) 0.00079831	(c, Pu ²⁴⁰) = 0.978	(c, Pu ²⁴⁰) = 1.137	(c, U ²³⁸) = 0.113	
(4) 0.00176745	(c, Pu ²⁴¹) = 0.963	(c, Pu ²⁴¹) = 1.121	(c, Pu ²³⁹) = 0.411	$\left[\frac{W_d(c, Pu^{239})}{W_p(c, Pu^{239})} \right] = 0.859$
(5) 0.00086293	(c, Pu ²⁴²) = 0.977	(c, Pu ²⁴²) = 1.137	(c, Pu ²⁴⁰) = 0.020	
(6) 0.00019983	(b, U ²³⁸) = 0.285	(b, U ²³⁸) = 0.383	(c, Pu ²⁴¹) = 0.349	$\left[\frac{W_p(c, U^{238})}{W_p(c, Pu^{239})} \right] = 1.020$
			(c, Pu ²⁴²) = 0.048	
			(b, U ²³⁸) = 0.059	

TABLE VI

EFFECTIVE DELAYED-NEUTRON FRACTION β_{eff} AND RELATED KINETICS DATA FOR 2500-LITER, PLUTONIUM A METAL, OXIDE, AND CARBIDE FAST REACTOR CORES

$\beta_{\text{eff}} ()$	$W_d ()$ WORTH OF DELAYED NEUTRONS IN CORE (c) AND BLANKET (b) FOR FISSIONABLE MATERIALS	$W_p ()$ WORTH OF PROMPT NEUTRONS IN CORE (c) AND BLANKET (b) FOR FISSIONABLE MATERIALS	$\frac{FIS()}{FIS(\text{tot})}$	WORTH RATIOS
--------------------------	---	--	----------------------------------	--------------

CORE: 2500 LITER, PLUTONIUM A, METAL; $\beta_p = 2.06918 \times 10^{-7}$; $\beta_{\text{eff}} = 0.00390745$

(1) 0.00008066	(c, U^{238}) = 0.986	(c, U^{238}) = 1.190	(c, tot) = 0.965	$\left[\frac{W_d(c, U^{238})}{W_p(c, Pu^{239})} \right] = 0.843$
(2) 0.00076188	(c, Pu^{239}) = 0.967	(c, Pu^{239}) = 1.169	(b, tot) = 0.035	
(3) 0.00070239	_____	_____	(c, U^{238}) = 0.183	
(4) 0.00142937	_____	_____	(c, Pu^{239}) = 0.782	
(5) 0.00068300	_____	_____	_____	$\left[\frac{W_d(c, Pu^{239})}{W_p(c, Pu^{239})} \right] = 0.827$
(6) 0.00024967	(b, U^{238}) = 0.233	(b, U^{238}) = 0.323	(b, U^{238}) = 0.035	$\left[\frac{W_p(c, U^{238})}{W_p(c, Pu^{239})} \right] = 1.018$

CORE: 2500 LITER, PLUTONIUM A, OXIDE; $\beta_p = 4.43106 \times 10^{-7}$; $\beta_{\text{eff}} = 0.00319037$

(1) 0.00007777	(c, U^{238}) = 1.054	(c, U^{238}) = 1.166	(c, tot) = 0.948	$\left[\frac{W_d(c, U^{238})}{W_p(c, Pu^{239})} \right] = 0.921$
(2) 0.00071051	(c, Pu^{239}) = 1.033	(c, Pu^{239}) = 1.145	(b, tot) = 0.052	
(3) 0.00060062	_____	_____	(c, U^{238}) = 0.090	
(4) 0.00113320	_____	_____	(c, Pu^{239}) = 0.858	
(5) 0.00048105	_____	_____	_____	$\left[\frac{W_d(c, Pu^{239})}{W_p(c, Pu^{239})} \right] = 0.903$
(6) 0.00018723	(b, U^{238}) = 0.281	(b, U^{238}) = 0.368	(b, U^{238}) = 0.052	$\left[\frac{W_p(c, U^{238})}{W_p(c, Pu^{239})} \right] = 1.019$

CORE: 2500 LITER, PLUTONIUM A, CARBIDE; $\beta_p = 3.37748 \times 10^{-7}$; $\beta_{\text{eff}} = 0.00346535$

(1) 0.00007892	(c, U^{238}) = 1.025	(c, U^{238}) = 1.172	(c, tot) = 0.954	$\left[\frac{W_d(c, U^{238})}{W_p(c, Pu^{239})} \right] = 0.890$
(2) 0.00072995	(c, Pu^{239}) = 1.006	(c, Pu^{239}) = 1.152	(b, tot) = 0.046	
(3) 0.0063957	_____	_____	(c, U^{238}) = 0.124	
(4) 0.00124666	_____	_____	(c, Pu^{239}) = 0.830	
(5) 0.00055871	_____	_____	_____	$\left[\frac{W_d(c, Pu^{239})}{W_p(c, Pu^{239})} \right] = 0.873$
(6) 0.00021134	(b, U^{238}) = 0.263	(b, U^{238}) = 0.353	(b, U^{238}) = 0.046	$\left[\frac{W_p(c, U^{238})}{W_p(c, Pu^{239})} \right] = 1.018$




FIG. II

ZERO POWER TRANSFER FUNCTION AMPLITUDE $|ZP(j\omega)|$ FOR LARGE PLUTONIUM (TYPE A AND C) OXIDE, CARBIDE AND METAL FUELED FAST REACTORS




FIG. III

ZERO POWER TRANSFER FUNCTION AMPLITUDE $|ZP(j\omega)|$ FOR LARGE PLUTONIUM (TYPE A AND B) OXIDE, CARBIDE AND METAL FUELED FAST REACTORS




FIG. IV

ZERO POWER TRANSFER FUNCTION PHASE ANGLE $\angle ZP(j\omega)$ FOR LARGE PLUTONIUM (TYPE A,B AND C) OXIDE, CARBIDE AND METAL FUELED FAST REACTORS. (800L, 1500L AND 2500L CORES)

CONCLUSIONS

Tables I through VI are arranged in such a way as to be largely selfexplanatory. One important quantity for stability studies is the value $1/\beta_{\text{eff}}$, as it determines the amplification in the plateau region of the zero-power transfer function. Some numbers for representative systems are

	β_{eff}	$1/\beta_{\text{eff}}$
EBR-I, Mark III (U^{235} - U^{238}) System	0.00683	146
Typical Large Fast (Pu- U^{238}) System	0.0035	286

We note that the value $1/\beta_{\text{eff}}$ is doubled up by going from the EBR-I, Mark III (U^{235} - U^{238}) system to a typical large fast (Pu- U^{238}) system.

Let us assume two reactors with equal heat transfer characteristics, sizes, and other pertinent data for the feedback function, i.e., $PK(j\omega)^{(13)}$ (power coefficient). Furthermore, we assume that the U^{235} - U^{238} system has a small bump in the load power transfer function $LP(j\omega)$, as shown in Fig. V. By replacing the U^{235} - U^{238} neutronics system with a Pu- U^{238} system, we would get a significant increase in the tendency towards resonance instability due to the doubling up of the amplification. This is, in fact, equivalent to a doubling up of the power level in the U^{235} - U^{238} system.




FIG. V

LOAD POWER TRANSFER FUNCTION FOR
FAST PLUTONIUM AND U^{235} REACTOR

The effect of raising power level in a linear system is studied in detail in Ref. 13. Bethe⁽¹⁵⁾ pointed out that it is relatively easy to correct such resonances if their mechanism is visualized during the design stages of the reactor. The core considered here is, of course, quite hypothetical, but it is well to remember that the neutronics characteristics of a plutonium system will introduce additional amplification because the delayed-neutron fractions of Pu^{239} are three times smaller than the delayed-neutron fractions of U^{235} .⁽¹³⁾ A considerable increase of β_{eff} is introduced in the Pu cases due to Pu^{240} , Pu^{241} , Pu^{242} , and U^{238} . Especially U^{238} contributes considerably, since the U^{238} fissions in the 1500-liter Pu (TYPE C) oxide core shown in Table V, for example, are close to 20% of the fissions of Pu^{239} in the core.

In the last column of Table V one notes for the above case that the worth of a delayed U^{238} neutron in the core is slightly higher than the worth of a delayed Pu^{239} neutron in the core.

From Figs. II and III one could single out fuel compositions and core sizes which would be worse than others with respect to introducing amplification, but it is felt that generalized conclusions should not be drawn at this point. Figure IV shows that the phase for these cores considered is not effected very much, as indicated by the variation between F and G.

ACKNOWLEDGEMENT

I would like to thank Dr. David Okrent for his help in getting a proper set of Fast Reactor Cores suitable for this study. The advice given to me by Drs. H. Hummel, D. Meneghetti, and V. Jankus during this study is very much appreciated.

Mr. L. Kvitek wrote the Fortran program to evaluate the effective delayed-neutron fraction β_{eff} , the prompt neutron lifetime ℓ_p , and worth functions. Mrs. S. Dean did all the voluminous 16-group hand calculations to check the computer results.

REFERENCES

1. L. Kvitek and H. A. Sandmeier, Multigroup Calculation of Effective Delayed Neutron Fraction β_{eff} , Prompt Neutron Lifetime ℓ_p , and Related Kinetic Parameters, IBM-704 Program 1188, Argonne National Laboratory.
2. J. Koerner and H. A. Sandmeier, The Transfer Function Problem Programmed for the IBM-650, BUM, ANL Code, (Nov 20, 1957).
3. S. Yiftah and D. Okrent, Some Physics Calculations on the Performance of Large Fast Breeder Power Reactors, ANL-6212 (Dec. 1960).
4. J. K. Long et al., Proceedings of the Second United Nations International Conference on the Peaceful Uses of Atomic Energy, Geneva, Switzerland, 12 119 (1958).
5. David Meneghetti, Recent Advances and Problems in Theoretical Analysis of ZPR-III Fast Critical Assemblies, Submitted for the Seminar on the Physics of Fast and Intermediate Reactors, Vienna, August 1961.
6. H. H. Hummel and A. L. Rago, An Accurate Treatment of Resonance Scattering in Light Elements in Fast Reactors, submitted for the Seminar on the Physics of Fast and Intermediate Reactors, Vienna, August 1961.
7. S. Yiftah, D. Okrent, and P. A. Moldauer, Fast Reactor Cross Sections - A Study Leading to a 16-Group Set, Pergamon Press (1960).
8. Samson A. Cox, Delayed Neutron Studies in the Thermal Neutron Induced Fission of Pu^{241} , Paper submitted to Phys. Rev., April 1961.
9. A. Smith, Argonne National Laboratory, private communication.
10. Reactor Physics Constants, Argonne National Laboratory Report ANL-5800.
11. G. R. Keepin, "Delayed Neutrons," Progress in Nuclear Energy, Vol. 1, Series 1, p. 196, (1956).
12. A. Stehney, Argonne National Laboratory, private communication.
13. H. A. Sandmeier, The Kinetics and Stability of Fast Reactors with Special Consideration of Nonlinearities, ANL-6014 (June 1959).
14. F. W. Thalgott et al., Stability Studies on EBR-I, Proceedings of the Second United Nations International Conference on the Peaceful Uses of Atomic Energy, Geneva, Switzerland 12, 242 (1958).
15. H. A. Bethe, Reactor Safety and Oscillator Test, APDA-117 (Oct 1956).

ARGONNE NATIONAL LAB WEST



3 4444 00011894 3