
June 1981 🗸



This is an informal report intended for use as a preliminary or working document



General Public Utilities • Electric Power Research Institute • U.S. Nuclear Regulatory Commission • U.S. Department of Energy

Quick Look Report Entry 4 Three Mile Island Unit 2 November 13, 1980



G.E. Eidam

Prepared for the U. S. Department of Energy Three Mile Island Operations Office Under Contract No. DE-AC07-76ID01570

DISTRIBUTION OF THIS COCUMENT IS UNLIMITED

GEND-INF-004 TIO-QLR

QUICK LOOK REPORT ENTRY 4 THREE MILE ISLAND UNIT 2. NOVEMBER 13, 1980

1

.

.

G. E. Eidam

Published June 1981

EG&G Idaho, Inc. Idaho Falls, Idaho 83415



Prepared for the U.S. Department of Energy Three Mile Island Operations Office Under Contract No. DE-ACO7-IDO1570

ABSTRACT

This report summarizes tasks performed during entry 4 at Three Mile Island Unit 2. During the entry into containment, which was made on November 13, 1980, additional beta and gamma surveys were conducted to supplement data acquired on previous entries. A decontamination test was completed on Elevation 305. Power receptables tested on Elevation 305 were deenergized, but receptacles on Elevation 347 were energized.

Still photography was acquired of Elevations 305 and 347. During the entry, 86 still photographs were taken. Videotaping (color and black and white) was done on Elevations 305 and 347, but lighting on both elevations was insufficient for high-quality video.

FOREWORD

The frequency of entries into containment at Three Mile Island Unit 2 is increasing, as are the complexity and number of tasks undertaken during each entry. For these reasons a brief summary of tasks and analytical results organized by entry is needed. This series of entry Quick Look Reports (QLRs) meets the need.

At the time of publication of this report, additional QLRs covering Entries 1 through 7 have been published. A QLR will be published following each subsequent entry.

CONTENTS

.

| ABSTRACT | ii |
|------------------------------|-----|
| FOREWARD | iii |
| ENTRY OVERVIEW | 1 |
| TASK SUMMARY | 2 |
| RADIATION SURVEY | 5 |
| Decontamination Test | 26 |
| Airborne Activity | 26 |
| SUMMARY OF ENTRY DEBRIEFINGS | 27 |

FIGURES

| 1. | Radiation survey locations on Elevation 305 for Entry 4, November 13, 1980. (Refer to Table 2.) | 16 |
|----|--|----|
| 2. | Radiation survey location on Elevation 305 for Entry 4, November 1?, 1980. This is the HPR-211 area survey, located on the enclosed stairwell wall, as indicated in Figure 1. (Refer to Table 3.) | 17 |
| 3. | Radiation survey locations on Elevation 305 for Entry 4, November 13, 1980. These survey locations are indicated on the plan view of the reactor building equipment hatch. (Refer to Table 4.) | 18 |
| 4. | Radiation survey locations on Elevation 305 for Entry 4, November 13,1980. These survey points are indicated on the plan view of the reactor building Personnel Airlock (PAL) #2. (Refer to Table 5.) | 19 |
| 5. | Radiation survey location on Elevation 305 (data points 16-28 are at Elevation 367) for Entry 4, November 13, 1980. (Refer to Table 6.) | 20 |
| 6. | Radiation survey locations at Elevation 347 for Entry 4, November 13,1980. These survey points are on the in-core instrumentation seal tabel. (Refer to Table 7.) | 21 |
| 7. | Location of decontamination test area on Elevation 305 made during Entry 4, November 13,1980. The airlock in the figure is #2 PAL | 22 |

TABLES

•

| 1. | Task summary for TMI-2 Entry 4, November 13, 1980 | 3 |
|----|--|----|
| 2. | Radiation survey, Elevation 305, November 13, 1980 | 6 |
| 3. | Radiation survey, HPR-211 on Elevation 305, November 13, 1980 | 8 |
| 4. | Radiation survey, equipment hatch on Elevation 305, November 13, 1980 | 9 |
| 5. | Radiation survey, Elevation 305, November 13, 1980 | 10 |
| 6. | Radiation survey, Elevation 347, November 13, 1980 | 12 |
| 7. | Radiation survey, Elevation 347, November 13, 1980 | 15 |
| 8. | Surface contamination from decontamination test on Elevation 305 | 23 |
| 9. | Airborne activity, November 13, 1980 | 25 |

ENTRY OVERVIEW

Entry 4 into the reactor building at Three Mile Island Unit 2 occurred on November 13, 1980. Twelve technicians working in three teams entered containment at 20-minute intervals, taking with them both video and still cameras and radiation survey equipment.

Entry 4 yielded additional beta and gamma survey data at both Elevation 305 and Elevation 347. Locations for these measurements were selected based on observations of personnel involved in previous entries as well as on study of still photographs acquired during those entries.

On Elevation 305 a preliminary decontamination test was conducted. The test involved smear and scrape samples taken before, during, and after a demineralizing water wash, a Radiac wash, and a Radiac scrub.

Power receptacles were tested on Elevation 305 as well as on Elevation 347. Receptacles on the lower level are powered from Elevation 282 (the basement level); these receptacles were all found to be deenergized. Receptacles on Elevation 347, on the other hand, were found to be carrying full power.

Data collected during entry 4 are presented in subsequent sections of this report.

1

.

A variety of tasks was performed during entry 4. These tasks are summarized in Table 1.

TABLE 1. TASK SUMMARY FOR TMI 2 ENTRY 4, NOVEMBER 13, 1980

. .

ω

Containment Temperature 69° (approximately 20.5°C) Containment Pressure - 0.2 in. Hg Relative Humidity <100% Airborne Activity <MPC

•

· · .

· ·

| Data Acquisition Task Number | Task Description | Task Accomplished | Problems Encountered | Comments Significant Findings |
|---------------------------------|---------------------------------------|---------------------------------------|---|--|
| 10A | Videotaped Elevation 305 | Videotaped Elevation 305 | Insufficient light for high-quality video | Four low-light-level cameras to be installed on Eleva- tion 305 in January- February 1981. |
| 31A, 31B | Videotaped Elevation 347 | Videotaped Elevation 347 | Insufficient light for high-quality video | Better flood lights to be installed on future entries; four low-light- level cameras to be installed on Eleva- tion 347 in January- February 1981 |
| N/A | Replace source range preamp | Not performed | Insufficient confi- dence in system and replacement part warranted further testing prior to installation | Installation to be made in January 1981 |
| N/A | Still photographs of Elevation 347 | Still photographs of Elevation 347 | None | None |

TABLE 1. (continued)

| Data Acquisition Task Number | Task Description | Task Accomplished | Problems Encountered | Comments Significant Findings |
|---------------------------------|--|--|----------------------|---|
| N/A | Investigate area around Personnel Airlock (PAL) #2 for for possible inter- mediate containment | Investigation completed | None | None |
| 4, 6, 1 22A, 22H | Conduct radiation surveys | Surveys completed | None | Improved survey of the in-core instrument table |
| N/A | Move fuel crane and assess access to core flood tanks from Elevation 347 | Fuel crane moved and access to A-core flood tank found possible, B-core flood tank very difficult | None | None |
| 42 | Decontamination experiment on Elevation 305 floor | Experiment completed | None | None |
| 38 | Paint chip samples | Obtained paint chip sample from reactor building dome | None | None |

(Section)

RADIATION SURVEY

Radiation was measured at many locations inside containment. Measurement locations, instruments used, and beta and gamma dose rates are presented in Table 2 through 7; survey points are indicated on Figures 1 through 6, which are associated with the tables.

Following these tables is a description of the decontamination test conducted during the entry; test location is shown in Figure 7, and readings are given in Table 8. Finally, Table 9 characterizes airborne activity.

| Data Acquisition Task Number | Location Figure 1 ^a | Instrument | Gamma Dose Rate (mrem/hr) | Beta Dose Rate (rad/hr) | Location |
|---------------------------------|-----------------------------------|------------|---------------------------------|-------------------------------|---------------------------------------|
| 1 | 1 | RO-2A | 450×b | C | South of PAL #2 |
| 1 | 2 | RO-2A | 1200 | | Elevator door |
|] | 3 | R0-2A | 600* | | In front of elevator |
| l | 4 | RO-2A | 600* | | In front of air coolers |
| 1 | 5 | RO-2A | 800 | 9.2 | Floor in front of air coolers |
| 1 | Ģ | RO-2A | 620 | | South side of D-ring wall |
| 4 | 7 | RO-2A | 3800 | | B-core flood tank piping |
| 6 | 8 | RO-2A | 2000 | 9.9 | Floor drain |
| ١ | 9 | RO-2A | 600 | | Near PAL #1 |
| 1 | 10 | RO-2A | 500 | 3.3 | Floor in front of PAL #1 |
| 1, | 11 | RO-2A | 600* | | North side of A-core flood tank |
|] | 12 | RO-2A | 400 | | D-ring near open stairwell |
| I | 13 | RO-2A | 3000 | 16.5 | Chains on floor near open stairwell |
| 1 | 14 | RO-2A | 1000 | | Near open stairwell |
| 1 | 15 | RO-2A | 300* | | Northwest section of reactor building |
| 1 | 16 | R0-24 | 200-390 | | Access fence to in-core chase |

TABLE 2. RADIATION SURVEY, ELEVATION 305, NOVEMBER 13, 1980

| Data Acquisition Task Number | Location Figure 1 ^a | Instrument | Gamma Dose Rate (mrem/hr) | Beta Dose Rate (rad/hr) | Location |
|---------------------------------|-----------------------------------|------------|---------------------------------|-------------------------------|---|
| 6 | 17 | RO-2A | 2000 | 26.4 | Floor drain |
| 1 | 18 | RO-2A | 1400 | C | Floor penetration on west side of D-ring |
| 1 | 19 | RO-2A | 1200 | | Floor penetration on west side of D-ring |
| 1 | 20 | RO-2A | 800* | | Seismic gap on east side of reactor building |
| 1 | 21 | RO-2A | 200* | | Northeast section of reactor building |
| 5 | 22 | RO-2A | 600 | 4.6 | Floor drain |

TABLE 2. (continued)

a. Figure 1 follows the table.

b. The asterisk (*) denotes general area readings--all others are contact readings.

c. The dash (--) indicates no reading taken.

7

| Data Acquisition Task Number | Location Figure 2 ^a | Instrument | Gamma Dose Rate (mrem/hr) | Beta Dose Rate (rad/hr) | Location |
|---------------------------------|-----------------------------------|------------|---------------------------------|-------------------------------|---|
| 1 | 1 | RO-2A | 250 | 0.165 | Just above HPR-211 mounting bar (contact) |
| 1 | 2 | RO-2A | 250 | 0.033 | Just below HPR-211 mounting bar (contact) |
| 1 | 3 | RO-2A | 400 | b | Area around HPR-211 at 1-ft (approxi- mately 30.5 cm) radius and 1 ft from wall |
| 1 | 4 | RO-2A | 280 | | Area around HPR-211 at 1-ft (apprcxi- mately 30.5 cm) radius and 1 ft from wall |
| ١ | 5 | RO-2A | 350 | | Area around HPR-211 at 1-ft (approxi- mately 30.5 cm) radius and 1 ft from wall |
| 1 | 6 | RO-2A | 480 | | Area around HPR-211 at 1-ft (approxi- mately 30.5 cm) radius and 1 ft from wali |
|] | 7 | RO-2A | 400 | | Area around HPR-211 at 1-ft (approxi- mately 30.5 cm) radius and 1 ft from wall |

TABLE 3. RADIATION SURVEY, HPR-211 ON ELEVATION 305, NOVEMBER 13, 1980

a. Figure 2 follows the table.

b. The dash (--) indicates no reading taken.

| Data Acquisition Task Number | Location Figure 3 ^a | Instrument | Gamma Dose Rate (mrem/hr) ^b | Beta Dose Rate (rad/hr) ^b |
|---------------------------------|-----------------------------------|------------|--|--|
| 42 | 1 | RO-2A | 200 | No β |
| 42 | 2 | RO-2A | 200 | 0.76 |
| 42 | 3 | RO-2A | 400 | Νοβ |
| 42 | 4 | RO-2A | 200 | No B |
| 42 | 5 | RO-2A | 150 | 1.1 |
| 42 | 6 | RO-2A | 200 | 1.1 |
| 42 | 7 | RO-2A | 500 | No ß |
| 42 | 8 | RO-2A | 500 | 7.2 |
| 42 | 9 | RO-2A | 1200 |]4.4 |

TABLE 4.RADIATION SURVEY EQUIPMENT HATCH ON ELEVATION 305,
NOVEMBER 13, 1980

÷,

a. Figure 3 follows the table.

.

1 b.

b. All readings are floor contact readings.

| Data Acquisition Task Number | Location Figure 4 ^a | Instrument | Gamma Dose Rate (mrem/hr) ^b | Beta Dose Rate (rad/hr) | Location |
|---------------------------------|-----------------------------------|------------|--|-------------------------------|--|
| 42 | 1 | RO-2A | 200 | 3.8 | See Figure 4 |
| 42 | 2 | RO-2A | 200 | 3.8 | See Figure 4 |
| 42 | 3 | RO-2A | 500 | 3.8 | See Figure 4 |
| 42 | 4 | RU-2A | 500 | 4.5 | See Figure 4 |
| 42 | 5 | RO-2A | 500 | 4.9 | See Figure 4 |
| 42 | 6 | RO-2A | 400 | 4.2 | See Figure 4 |
| 42 | 7 | RO-2A | 300 | 3.4 | See Figure 4 |
| 42 | 8 | RO-2A | 200 | 1.1 | See Figure 4 |
| 42 | 9 | RO-2A | 500 | 3.9 | See Figure 4 |
| 42 | 10 | RO-2A | 200 | 5.3 | See Figure 4 |
| 42 | 11 | RO-2A | 300 | 4.6 | See Figure 4 |
| 42 | 12 | R0-2A | 500 | 5.7 | See Figure 4 |
| 42 | 13 | RO-2A | 400 | 3.8 | See Figure 4 |
| 42 | 14 | RO-2A | 500 | 3.8 | Prior to decontamination test operations |
| 42 | 14 | RO-2A | 400 | 2.3 | After water wash |
| 42 | 14 | R0-2A | 400 | 2.3 | After Radiac wash |

-1

• ·

| Data Acquisition Task Number | Location Figure 4 ^a | Instrument | Gamma Dose Rate (mrem/hr) ^b | Beta Dose Rate (rad/hr) | Location |
|---------------------------------|-----------------------------------|------------|--|-------------------------------|---|
| 42 | 14 | RO-2A | 400 | 1.1 | After Radiac scrub |
| 42 | 15 | RO-2A | C | 2.3 | See Figure 4: Contact reading taken before placing rubber matopen window only |

0.5

R0-2A

TABLE 5. (continued)

42

a. Figure 4 follows the table.

b. All readings are floor contact readings.

15

c. The dash (--) indicates no reading taken.

a second residence and the second second

See Figure 4: Contact reading taken after placing rubber mat (thickness approximately 3/8 in., or just less than 1 cm)--open window only

| Data Acquisition Task Number | Location Figure 5 ^a | Instrument | Gamma Dose Rate (mrem/hr) | Beta Dose Rate (rad/hr) | Location |
|---------------------------------|-----------------------------------|------------|---------------------------------|-------------------------------|---|
| 22A | 1 | Teletector | 200*b | C | Inside of elevator shaft |
| 22A | 2 | R0-2A | 500* | | Southside of enclosed stairwell |
| 22A | 3 | R0-2A | 500* | | Northeast corner of equipment hatch deck plate |
| 22A | 4 | R0-2A | 500* | | West side of equipment hatch deck plate |
| 22A | 5 | R0-2A | 500* | | Southwest corner of equipment hatch deck plate |
| 22A | 6 | R0-2A | 500* | | B-core flood tank grating |
| 22A | 7 | RO-2A | 350* | | First landing of open stairwell |
| 22A | 8 | RO-2A | 300 | 5.6* | Gap between stairs of open stairwell |
| 22H | 9 | RO-2A | 1000 | 9.9 | Floor drain |
| 22A | 10 | RO-2A | 100* | | Near deck plate for A-core flood tank |
| 22A | 11 | RO-2A | 150* | | Deck plate over A-core flood tank |
| 22A | 12 | RO-2A | 200* | | East of A-core flood tank |
| 22H | 13 | RO-2A | 350* | 2.2 | Floor drain |
| 22A |]4 | R0-2A | 150* | | Second landing of open stairwell |

.

. •

TABLE 6. (continued)

•

| Data Acquisition Task Number | Location Figure 5 ^a | Instrument | Gamma Dose Rate (mrem/hr) | Beta Dose Rate (rad/hr) | Location |
|---------------------------------|-----------------------------------|------------|---------------------------------|-------------------------------|--|
| 22A | 15 | R0-2A | 100* | | Top landing of open stairwell (Elevation 367) |
| 22A | 16 | RO-2A | 100* | 0.594* | Top of east D-ring (Elevation 367) |
| 22A | 17 | RO-2A | 100* | 0.594* | Top of east D-ring (Elevation 367) |
| 22A | 18 | RO-2A | 200* | 0.825* | Arm's reach into east D-ring (Elevation 367) |
| 22A | 19 | R0-2A | 300 | 8.9 | Top of steel support beam (Elevation 367) |
| 22A | 20 | R0-2A | 100* | 0.594* | Top of D-ring on south side (Elevation 367) |
| 22A | 21 | R0-2A | 600* | 1.650* | Arm's reach into east D-ring (Elevation 367) |
| 22A | 22 | R0-2A | 150* | 0.165* | South walkway between D-rings (Elevation 367) |
| 22A | 23 | R0-2A | 700* | 0.330* | Arm's reach into west D-ring (Elevation 367) |
| 22A | 24 | R0-2A | 250 | 9 | Top of steel support ring (Elevation 367) |
| 22A | 25 | R0-2A | 500* | No β* | Arm's reach into west D-ring (Elevation 367) |

а. — С

۰ ،

TABLE 6. (continued)

| Data Acquisition Task Number | Location Figure 5 ^a | Instrument | Camma Dcse Rate (mrem/hr) | Beta Dose Rate (rad/hr) | Location |
|---------------------------------|-----------------------------------|------------|---------------------------------|-------------------------------|--|
| 22A | 26 | RO-2A | 300 | 8.9 | Top of steel support ring (Elevation 367) |
| 22A | 27 | RO-2A | 1500* | No β* | Arm's reach into west D-ring (Elevation 367) |
| 22A | 28 | R0-2A | 200* | 660 | North walkway between D-rings (Elevation 367) |

14

a. Figure 5 follows the table.

.

.

b. The asterisk (*) denotes general area readings--all others are contact readings.

c. The dash (--) indicates no reading taken.

| Data Acquisition Task Number | Location Figure 6 ^a | Instrument | Gamma Dose Rate (mrem/hi, | Beta Dose Rate (rad/hr) | | | | | |
|---------------------------------|-----------------------------------|------------|---------------------------------|-------------------------------|--|--|--|--|--|
| 22H | 1 | RO-2A | 5,000*b | 4.95* | | | | | |
| 22H | | RO-2A | 5,000 | >149 | | | | | |
| 22H | 2 | RO-2A | 1,500* | 11.95* | | | | | |
| 22H | | RO-2A | 10,000 | >132 | | | | | |
| 22H | 3 | RO-2A | 10,000* | 16.5* | | | | | |
| 22H | | RO-2A | 15,000 | >115.5 | | | | | |
| 22H | 4 | RO-2A | 1,800* | 10.5* | | | | | |
| 22H | | RO-2A | 2,000 | 9.9 | | | | | |
| 22H | 5 | RO-2A | 10,000* | 13.5* | | | | | |
| 22H | | RO-2A | 3,500 | >153.4 | | | | | |


TABLE 7. RADIATION SURVEY, ELEVATION 347, NOVEMBER 13, 1980

a. Figure 6 follows the table.

٠.


ł

b. The asterisk (*) denotes waist level readings--all others are contact readings.



PLAN VIEW, ELEVATION 305


Figure 1. Radiation survey locations on Elevation 305 for Entry 4, November 13, 1980. (Refer to Table 2.)



HPR-211 Area Survey

Located on Closed Stairwell wall (See Figure 1) Radiation Survey Points November 13, 1980 Entry


Figure 2. Radiation survey location on Elevation 305 for Entry 4, November 13, 1980. This is the HPR-211 area survey, located on the enclosed stairwell wall, as indicated in Figure 1. (Refer to Table 3.)



Reactor Building Equipment Hatch

Plan View Radiation Survey Points November 13, 1980 Entry

Figure 3. Radiation survey locations on Elevation 305 for Entry 4, November 13, 1980. These survey locations are indicated on the plan view of the reactor building equipment hatch. (Refer to Table 4.)




공항하는 것

Reactor Building Personnel Airlock #2

Plan View Radiation Survey Points November 13, 1980 Entry


Figure 4. Radiation survey locations on Elevation 305 for Entry 4, November 13,1980. These survey points are indicated on the plan view of the reactor building Personnel Airlock (PAL) #2. (Refer to Table 5.)



PLAN EL 347'-6"

Radiation Survey Points November 13, 1980 Entry (Data points 16 through 28 @ El. 367')

Figure 5. Radiation survey location on Elevation 305 (data points 16-28 are at Elevation 367) for Entry 4, November 13, 1980. (Refer to Table 6.)



€.5

Incore Instrumentation Seal Table


Plan View (See Figure 5) Radiation Survey Points November 13, 1980 Entry

Figure 6. Radiation survey locations at Elevation 347 for Entry 4, November 13,1980. These survey points are on the in-core instrumentation seal tabel. (Refer to Table 7.) Smear samples 1 through 8 were taken in the center of a two foot by two foot area. This area is located on Elevation 305' between the #2 PAL entry ramp and the D-ring as shown below. Sequence of the smears was as follows:

> Smears 1 and 2 - prior to any decon operations Smears 3 and 4 - after deminerlized water wash Smears 5 and 6 - after Radiac wash Smears 7 and 8 - after Radiac scrub

Scrape Sample 9 was taken outside the decon area. Scrape Sample 10 was taken in the decon area after the final smears.

Speciman II is a paint chip found on the floor at the 347' Elevation. It came from the dome of the reactor building (approximately 300 cm²).



Reactor Building Personnel Airlock #2

Figure 7. Location of decontamination test area on Elevation 305 made during Entry 4, November 13,1980. The airlock in the figure is #2 PAL.

| Data Acquisition Task Number | Specimen ^{a,b,c} | Gross Sample Number | Gross alpha (µCi)(B&W) ^d ,e | Gross beta & gamma (µCi)(B&W) ^{d,e} | Sr ⁹⁰ /γ ⁹⁰ (μCi) (SAI) ^d ,f | Cs ¹³⁴ (µCi) (B&W/SAI) ^{e,f} | Cs ¹³⁷ (µCi) (B&W/SAI) ^{e,f} |
|------------------------------------|---------------------------|---------------------------|---|--|---|--|--|
| 42 | 1 | 52503 | | | 2.3E-1 | 1.7E+0/ 1.0E+0 | 1.2E+1/ 6.4E+0 |
| 42 | 2 | 52504 | | | 5.7E-1 | 1.3E+0 7.0E-1 | 8.9E+0/ 4.2E+0 |
| 42 | 3 | 52505 | | | 5.2E-3 | 1.8E-2/ 1.4E-2 | 1.4E-1/ 1.1E-1 |
| 42 | 4 | 52506 | | | 1.4E-2 | 2.6E-2/ 2.1E-2 | 1.9E-1/ 1.6E-1 |
| 42 | 5 | 52507 | <2.7E-79 | 3.2E-2 | 5.6E-3 | 7.8E-3/ 7.6E-3 | 5.8E-2/ 5.3E-2 |
| 42 | 6 | 52508 | <2.7E-79 | 3.4E-2 | 7.7E-4 | 3.8E-3/ 1.8E-3 | 2.85-2/ 1.36-2 |
| 42 | 7 | 52509 | <2.7E-79 | 8.7E-3 | 3.3E-3 | 8.5E-3/ 5.8E-3 | 6.3E-2/ 4.1E-2 |
| 42 | 8 | 52510 | <2.7E-79 | 1.0E-2 | 1.2E-3 | 5.1E-3/ 2.2E-3 | 3.6E-2/ 1.5E-2 |
| 42 | 9 | 52511 | | | | 3.4E-1/ | 2.4E+0/ |

•

TABLE 8. SURFACE CONTAMINATION FROM DECONTAMINATION TEST ON ELEVATION 305

| Data Acquisition Task Number | Specimen ^{a,b,c} | Gross Sample Number | Gross alpha <u>(µCi)(B&W)^d,</u> e | Gross beta & gamma (µCi)(B&W) ^d ,e | Sr ⁹⁰ /y ⁹⁰ (µCi) (SAI) ^d ,f | Cs ¹³⁴ (µCi) (B&W/SAI) ^{e,f} | Cs ¹³⁷ (µCi) (B&W/SAI) ^{e,f} |
|------------------------------------|---------------------------|---------------------------|---|---|---|--|--|
| 42 | 10 | 52512 | | | | 5.0E-2/ | 3.6E-1/ |
| 38 | յլի | 52513 | | | 4.8E-3 | 1.6E-2/ 1.6E-2 | 1.1E-1/ 1.1E-1 |

a. See Figure 7 for locations at which samples were taken.

b. For specimens 1 through 8 readings are per swipe of approximately 100 cm² (15.5 in.²).

c. For specimens 9 and 10 readings are for scrape samples of approximately 100 cm².

- d. No analysis performed.
- e. B&W is Babcock and Wilcox.
- f. SAI is Science Applications Incorporated.
- g. The less than symbol (<) implies result below Lower Limit Detectable (LLD).
- h. Specimen 11 is a paint chip from the reactor building dome.

TABLE 9. AIRBORNE ACTIVITY, NOVEMBER 13, 1980

.

| Data Acquisition Task Number | Specimen ^a | Sample Number | I-31 (µCi/ml) (B&W) ^{b,c} | Cs-134 (uCi/m1) (B&W) ^b | Cs-137 (µCi/ml) (B&W) ^b | Co-58 (uCi/ml) (B&W) ^{b,c} | Co-60 (µCi/ml) (B&W) ^{b,c} | Sr-90 (uCi/ml) (SAI) ^d | Gross alpha (uCi/ml) (B&W) ^{b,c,d} | Gross alpha & gamma (µCi/ml) (B&W) ^C | Comments |
|------------------------------------|---------------------------|------------------|--|--|--|---|---|---|--|---|---|
| N/A | BZA | 52320 | <9.3E-10 | 2.0E-8 | 1.4E-7 | <3.7E-10 | <3.9E-10 | 4.6E-9 | e | 1.17E-7 | |
| N/A | BZA | 52321 | <7.18-10 | 1.4F-8 | 1.0E-7 | <2.2E-10 | <2.8E-10 | 3.4E-9 | | 7.69E-8 | |
| N/A | B; 4 | 52322 | <5.4E-10 | 1.7E-8 | 1.3E-7 | <2.6E-10 | <1.4E-10 | 4.1E-9 | | 8.28E-8 | |
| N/A | BZA | 52348 | <4.0E-10 | 7.7E-9 | 6.4E-8 | <1.7E-10 | <1.5E-10 | 2.5E-9 | | 6.08E-8 | |
| N/A | BZA | 52349 | <8.4E-10 | 1.68E-10 | 1.1E-8 | <2.5E-10 | <4.2E-10 | 4.3E-9 | 2.33E-12 | 9.03E-8 | |
| N/A | BZA | 52350 | <7.9E-10 | 1.8E-8 | 1.4E-7 | <3.8E-10 | <2.6E-10 | 4.9E-9 | 2.33E-12 | 1.14E-7 | |
| N/A | BZA | 52351 | <3.5E-10 | 1.2E-8 | 9.4E-8 | <1.5E-10 | <7.7E-11 | 6.4E-9 | 1.22E-12 | 6.96E-8 | |
| N/A | BZA | 52352 | <4.0E-10 | 7.1E-9 | 4.7E-8 | <1.5E-10 | <2.2E-10 | 2.5E-9 | 1.22E-12 | 4.57E-8 | |
| N/A | BZA | 52353 | <3.8E-10 | 7.2E-9 | 5.7E-8 | <1.4E-10 | <1.4E-10 | 4.4E-9 | 1.22E-12 | 5.39E-8 | |
| N/A | BZA | 52354 | <2.6E-10 | 6.5E-9 | 5.0E-8 | <1.2E-10 | <7.7E-11 | 3.18-9 | 1.22E-12 | 5.02E-8 | |
| N/A | BZA | 52355 | <3.7E-10 | 5.5E-9 | 3.6E-8 | <1.3E-10 | <2.2E-10 | 2.1E-9 | 1.22E-12 | 3.26E-8 | |
| N/A | BZA | 52326 | <3.5E-10 | 5.5E-9 | 4.3E-8 | <1.3E-10 | <1.4E-10 | 3.1E-9 | 1.22E-12 | 4.35E-8 | |
| N/A | High-volume air sample | 52319 | <6.2E-11 | 4.6E-9 | 3.3E-8 | <2.1E-11 | <1.0E-11 | 1.9E-9 | 4.52E-12 | | Sample was taken 18 in. (approximately 47 cm) from |

.

Sample was taken 18 in. (approximately 47 cm) from the south D-ring wall and approximately 18 in. above the floor. .

,

a. Lapel air sample.

b. B&W is Babcock and Wilcox.

c. The less than symbol (<) implies result below Lower Limit Detectable (LLD).

d. S41 is Science Applications Incorporated.

e. The dash (--) indicates no analysis performed.

.

Decontamination Test

Smear samples 1 through 8 were taken in the center of a test area of approximately 3700 cm² (4 ft²). This area is located on Elevation 305 between the #2 PAL entry ramp and the D-ring as shown in Figure 7. Sequence of the smears was as follows:

Smears 1 and 2: prior to any decontamination operations
Smears 3 and 4: after demineralized water wash
Smears 5 and 6: after Radiac wash
Smears 7 and 8: after Radiac scrub.

Scrape sample 9 was taken outside the decontamination area. Scrape sample 10 was taken in the decontamination area after the final smears. Sample 11 is a paint chip found on the floor at Elevation 347. The chip came from the reactor building dome and is approximately 300 cm^2 (approximately 46.5 in.²).

Data from the test are presented in Table 8.

Airborne Activity

Air samples were taken during entry 4. Airborne activity data are presented in Table 9.

SUMMARY OF ENTRY 4 DEBRIEFINGS

Twelve men participated in entry 4. Most noted apparent superficial damage (e.g., bowed elevator door, mud and rust stains at various locations, missing power rail for the polar crane).

Among other comments made during debriefing are the following:

- After measurement, it appears very feasible to build a new airlock inside the equipment airlock. Demineralized water connections with Hanson fittings exist at both corners of the D-ring.
- The grating by the B-core flood tank is so heavy that even two men may not be able to lift it.
- Pressure on the A steam generator registered approximately 2.5 lb on the local gauge, the same reading as is indicated in the M2O area.
- Radiation levels were higher on the B steam generator side than on the A steam generator side.
- Gamma radiation appears to be coming through the floor of Elevation 305. During the decontamination test, the gamma radiation dropped significantly after the initial wash, but the Radiac wash and scrub brought no further reduction.
- Lighting levels inside the reactor building are inadequate for high-quality video. The portable flood lights used were difficult to maneuver and caused reflections. Some locations could not be illuminated at all, and the cameras could not gain access to some areas.

27