



Westinghouse Update August 2021

August 2021

Changing the World's Energy Future

Joshua E Hansel



INL is a U.S. Department of Energy National Laboratory operated by Battelle Energy Alliance, LLC

DISCLAIMER

This information was prepared as an account of work sponsored by an agency of the U.S. Government. Neither the U.S. Government nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness, of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. References herein to any specific commercial product, process, or service by trade name, trade mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the U.S. Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the U.S. Government or any agency thereof.

Westinghouse Update August 2021

Joshua E Hansel

August 2021

**Idaho National Laboratory
Idaho Falls, Idaho 83415**

<http://www.inl.gov>

**Prepared for the
U.S. Department of Energy
Under DOE Idaho Operations Office
Contract DE-AC07-05ID14517**



U.S. DEPARTMENT OF
ENERGY

Nuclear Energy



Westinghouse Update

August 2021



Sockeye Activities Since Last Update

Nuclear Energy

■ Conference paper submitted

- Introduced new conduction model based on controls
- Modeled SAFE-30 experiment with new conduction model
- Repeated SAFE-30 experiment with flow model improvements
- Repeated sonic limit assessment with correct reference temperature
- Repeated some previously shown results

■ Summer intern performed some validation work

- SPHERE (in progress)
- UMich NEUP experiments (in progress)

■ Wetting dynamics (now testing)




Improvements Shown in Paper

Nuclear Energy


■ SAFE-30 flow model:

- Temperature-dependent contact angle
- Minor robustness improvements
- Now gets to 18000 s instead of 9575 s:



■ Sonic limit assessment:



- Used evaporator endcap temperature instead of average core temperature:





New Conduction Model Approach

- The *old* conduction model approach limits the heat rate at the cladding boundary.
- The *new* conduction model approach limits the heat rate at the evaporator exit.
 - The thermal conductivity of the vapor core is controlled: $k_{core,min} \leq k_{core} \leq k_{core,max}$.
 - Power through evaporator exit, $\dot{Q}_{evapexit} = \int_{S_{evapexit}} -k_{core} \frac{\partial T}{\partial x} dS$ is compared to analytic limits.
 - k_{core} is modified to renormalize $\dot{Q}_{evapexit}$ for next time step to be equal to \dot{Q}_{limit} (within bounds of k_{core})
 - Results for SAFE-30:





Validation Progress: SPHERE


■ The heat pipe used in SPHERE contains some amount of argon (non-condensable gas).

- Amount is unknown, but it can be estimated from measured temperature data:
 - Estimate NCG front position and thus volume of NCG
 - Use Dalton's law of partial pressures and flat-front approximation to work out NCG mass


■ Conduction model needs modification to account for NCGs.

- Dynamically determine NCG front location.
- Use small core thermal conductivity in NCG pool.
- Such a model is in progress.

Thermocouple
values during
transient:



Spatial
temperature
profile during
peak power:







- **Currently Sockeye does not include physics to draw fluid up the wick.**
 - The advection terms in the PDEs do not consider capillary pressure, only relaxation source terms.
 - A no-heat-transfer test case confirms that the wick is not drawing up fluid from a pool.
- **The physical ramifications:**
 - Gravity may prematurely drain the wick.
 - Dryout may be predicted prematurely when gravity is not replenishing fluid.
- **The approach to solving this is to modify the PDEs to add a capillary pressure gradient term.**
- **Preliminary tests show fluid movement up the wick in the no-heat-transfer test case.**
- **The rate of rise up the wick has not yet been examined.**