

Performance Validation of a ThermallyIntegrated 50 kW High Temperature Electrolyzer System

May 2024

Amey Shigrekar, Temitayo Olayemi Olowu, Shaleena Jaison, Trina Marie McCormick, Micah Joel Casteel, Tyler L Westover





DISCLAIMER

This information was prepared as an account of work sponsored by an agency of the U.S. Government. Neither the U.S. Government nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness, of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. References herein to any specific commercial product, process, or service by trade name, trade mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the U.S. Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the U.S. Government or any agency thereof.

Performance Validation of a ThermallyIntegrated 50 kW High Temperature Electrolyzer System

Amey Shigrekar, Temitayo Olayemi Olowu, Shaleena Jaison, Trina Marie McCormick, Micah Joel Casteel, Tyler L Westover

May 2024

Idaho National Laboratory Idaho Falls, Idaho 83415

http://www.inl.gov

Prepared for the U.S. Department of Energy Under DOE Idaho Operations Office Contract DE-FOA-0002300 Apr. 25, 2024

A. Shigrekar, M. Casteel, T. Westover, T. Olowu, S. Jaison, T. Davis (INL)
D. Larsen, J. Hartvigsen, E. Elangovan, E. Pilstl, A. Gomez, A. Yarosh (OxEon)

Performance Validation of a Thermally Integrated 50 kW High Temperature Electrolyzer System

DE-FOA-0002300: Grant 13163665 2024 FECM/NETL Spring R&D Project Review Meeting

This presentation does not contain any proprietary, confidential or otherwise restricted information




Project Goals

- Accumulate ~3,000 hrs operating a reversible solid oxide electrolysis (rSOC) system
 - A SOC system at INL will be modified for reversible operations:
 - 30-kW electrolysis mode/10-kW fuel cell mode
 - SOC stacks will incorporate improved catalyst in fuel electrode
 - Operation of rSOC system will be coupled to a steam generator programmed to mimic an industrial source of low-grade heat
- Thermodynamic analysis will demonstrate potential to achieve > 85% system efficiency in electrolysis mode
- Technoeconomic analysis (TEA) will demonstrate potential to produce hydrogen at a cost of \$2/kg on a cost of electricity of \$30/MWhr.

Project Start Date: 10/01/2020


Project End Date: 08/30/2024



Relevance

DE-FOA-0002300 AIO 2:

- Improving the cost, performance and reliability of reversible rSOC systems for clean hydrogen and clean power production
- rSOC systems have opportunities to enter the marketplace but <u>need proven system cost</u>, <u>performance</u>, <u>and reliability</u>
- rSOC systems can use the same system components (stacks, heat exchangers, piping, power converters, etc.) to <u>reduce capital cost</u> and maximize equipment capacity factor (% of time at maximum power)
- May be deployed at small scale to meet needs of diverse users for clean energy utilization, storage, and supply (supports environmental justice)
 - Full design of BOP system will be open-access



Approach

Task 1: Revise Project Management Plan

Task 2: Stack manufacturing (OxEon)

Task 3: e² Catalyst Development (MIT)


Task 4: Reconfigure 50 kW SOC system


Task 5: System integration and testing


Task 6: Technoeconomic Analysis

Task 7: Data analysis

Task 8: Final Report










Eeyond Current Potential

Utah R&D/Mfg Facility – Founded in 2017 after successful 30-year collaboration with founders of previous affiliation

- New 24,000 ft² (2230 m²) office, laboratory, and manufacturing facility
- NASA, DOE, DOD and Commercial funding
- Tape casting, cell and stack production, and testing
- End-to-end power to synfuels pilot plant in operation






Solid Oxide Fuel Cell and Electrolysis Stacks

- Longest running solid oxide fuel cell & electrolysis group in world
- Only flight qualified, TRL 9 SOEC unit in history
- 30kW/10kW reversible system test program in process


Fuel Reformation and Generation

- Plasma Reformer H₂ and Syngas for flare curtailment
- Fischer-Tropsch Reactors Modular design for transportation fuel production from H₂ and Syngas




System Design and Integration


- Standard SOEC/SOFC design
 - High temperature heat exchangers (HXers) on fuel and air streams
 - HXer bypasses for incoming fuel and air streams in FC model
 - Trim heaters for EC mode
 - Fuel Condenser to separate water from product H2
 - H2 recycle loop with blower
- Steam from electric boiler or nonfired boiler



System Design & Integration


- High temperature piping design
 - Separate stack & HXer modules
 - Piping components supported on springs to allow thermal expansion; no bellows flanges






System Design & Integration

- 30 kW rSOC system located in custom 20 ft container with doors on three walls
- 12 OxEon SOEC stacks arranged in quad configurations on manifold





OxEon SOEC stacks on manifold





OxEon Stacks





Challenges and Barriers

- Manufacturing delays
 - COVID-19 issues have slowed procurement
 - Some components have 18 30-week lead time.
 - Loss of critical personnel
 - Design issues
 - Excessive heat loss
 - Misalignment of the lid
 - Lack of recirculation




System Status 1

- Design build is complete
 - All the necessary components and instrumentation has been installed on the system
 - Instrumentation ring out with data acquisition is complete



System Status 2

- Subsystem tests have been performed to verify operation
 - Fuel, sweep air, electrical, thermal, safety, comms etc.
- Control strategy is 90% complete
 - Current focus is on state transition flow



Summary

- Task 2 Stack manufacturing
 - Manufacturing by OxEon is complete
- Task 3 e² Catalyst development
 - Catalyst development complete
- Task 4 Reconfigure 50-kW SOEC system
 - Engineering complete
 - Last major item to be received is the high temperature piping system expected ~ Nov. 8, 2002
- Task 5 System integration and testing
 - System integration expected ~ Dec. 15, 2022
 - System will be instrumented to measure thermodynamic performance
 - System will be operated for 3,000 hrs (Jan. Jul. 2023)
- Task 6 Technoeconomic & thermodynamic analysis (TEA)
 - Thermodynamic analysis will demonstrate potential to achieve > 85% system efficiency in SOEC mode
 - TEA will show potential to produce H₂ at \$2/kg on a cost of electricity of \$30/MWhr.







Battelle Energy Alliance manages INL for the U.S. Department of Energy's Office of Nuclear Energy. INL is the nation's center for nuclear energy research and development, and also performs research in each of DOE's strategic goal areas: energy, national security, science and the environment.