



EVOLUTION OF SPACE REACTOR QUALIFICATION METHODS AND A PATH FORWARD FOR NEW SPACE REACTORS UNDER CONSIDERATION

Changing the World's Energy Future

Andrew John Zillmer, Stephen Johnson, Dasari Rao



INL is a U.S. Department of Energy National Laboratory operated by Battelle Energy Alliance, LLC

DISCLAIMER

This information was prepared as an account of work sponsored by an agency of the U.S. Government. Neither the U.S. Government nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness, of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. References herein to any specific commercial product, process, or service by trade name, trade mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the U.S. Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the U.S. Government or any agency thereof.

EVOLUTION OF SPACE REACTOR QUALIFICATION METHODS AND A PATH FORWARD FOR NEW SPACE REACTORS UNDER CONSIDERATION

Andrew John Zillmer, Stephen Johnson, Dasari Rao

March 2020

**Idaho National Laboratory
Idaho Falls, Idaho 83415**

<http://www.inl.gov>

**Prepared for the
U.S. Department of Energy
Under DOE Idaho Operations Office
Contract DE-AC07-05ID14517**

EVOLUTION OF SPACE REACTOR QUALIFICATION METHODS AND A PATH FORWARD FOR NEW SPACE REACTORS UNDER CONSIDERATION



www.inl.gov

Andrew Zillmer – Idaho National Laboratory
Dr. Stephen Johnson – Idaho National Laboratory
Dr. Dasari Rao – Los Alamos National Laboratory


Overview

- General Space Reactor Systems
- Component and System Qualification
 - SNAP
 - SP-100
 - TOPAZ
 - Prometheus
- Presidential Memorandum
- Future Space Reactor Qualification

General Reactor System Components


- Reactor – generates thermal energy
- Shielding - reduces radiation exposure to equipment and personnel
- Primary heat transport system – transfers heat from the reactor to the power conversion system
- Power conversion system – converts heat to electricity
- Heat rejection system – rejects heat from the power conversion system to the environment
- Power management and distribution system – controls the distribution of power from the conversion system
- Control system – controls system power demand for the space reactor system

General Power Reactor Layout



SNAP 10A – Development and Flight Test Systems

- 11 systems were built for system development and flight testing
- PSM-1, 2, 3 – prototype system tests that provided early system design information that could be incorporated back into the system design
- FSM-1, 2, 3 – electrically heated qualification tests that allowed for practice in prelaunch operations, demonstrated component interoperability, and electrical compatibility with the upper stage
- FS-1 – nuclear qualification tests
- FS-2 – became FSM-4 non-nuclear qualification test using flight components
- FS-3, 4, 5 – flight systems



SNAP Program Ground Testing Facilities



- Many facilities for component and system testing were located on the Energy Technology and Engineering (ETEC) site north of Los Angeles, CA
- ETEC facilities enabled concurrent engineering on development systems
- Additional testing was performed at the Idaho National Engineering Laboratory (INEL) and Oak Ridge National Laboratory (ORNL)
- ETEC Facilities included
 - Building 013 – hardware checkout
 - Building 025 – demonstration of remote handling tools
 - Building 023 – development, endurance testing, qualification, and acceptance testing of liquid metal components
 - Building 027 – component qualification testing and system checkout
 - Building 042 – shield fabrication and test
 - Building 057 – development and demonstration of hardware fixtures and ground support equipment
 - Building 065 – thermoelectric component life testing, qualification testing, and thermal vacuum chamber testing
 - Building 066 – control and instrumentation component life testing, qualification testing, and acceptance testing

SNAP Program Ground Testing Critical Facilities

- Component development and system tests were performed primarily at ETEC
 - Building 10 / 4010– criticality testing at low power levels
 - Building 012 / 4012– core and reactor zero power level testing
 - Building 019 / 4012 – flight unit acceptance testing with underground thermal vacuum chamber
 - Building 024 / 4024 – nuclear tests in space environment chamber
 - Building 373 / 4373 – critical tests for ZrH fuel development

SP-100 Component System & Testing

- Materials Qualification
 - UN fuel irradiation at Fast Flux Test Facility (FFTF) and Experimental Breeder Reactor II (EBR II)
- Critical Facilities
 - Los Alamos Critical Experiment Facility (TA-18) was planned for benchmarking of nuclear cross sections
 - FFTF and EBR II were identified for fast neutron spectrum materials testing
- Ground Testing
 - Nuclear Assembly Test (NAT) facility at DOE Hanford site was to built inside the existing building 309 for prototype reactor assembly
 - Converter Pump Assembly Test (CPAT) in Valley Forge, PA was to perform electrically heated non-nuclear system tests



TOPAZ Component and System Qualification

- TOPAZ II system development began in 1969 in USSR and built 26 units
- Qualification test program in USSR included
 - Thermal management tests
 - Mechanical tests
 - Electrical heat source simulation
 - Ground nuclear tests
- US-Russian cooperative program began in late 1990's to modify a TOPAZ II system for use in an electric propulsion system
 - Key changes were made to ensure that the core will remain subcritical on reentry

TOPAZ system qualification


- Actual qualification on the TOPAZ II systems is classified
 - Process was likely similar to MIL-STD-1540B approach for U.S. spacecraft qualification
 - Russian approach tended to use qualification of similar hardware from production runs rather than actual flight hardware
 - Likely had significantly less environmental testing on flight units as compared to U.S. qualification processes
- Modifications identified during transition of the program to the U.S. included
 - Complete flight qualification
 - Replace forced convection cooling with radiative cooling
 - Replace control system with a U.S. microprocessor-based design
 - Change core loading to eliminate change of nuclear criticality when immersed in water

TOPAZ system qualification in U.S.

- Two units underwent non-nuclear testing at the Phillips Laboratory
- Testing included
 - Modal test to determine dynamic characteristics
 - Thermal vacuum tests from with electrical heaters to generate 0 to 95 kWth to create a performance baseline and demonstrate the NaK system loop's integrity
 - Mechanical tests including mass properties (CG, MOI), load testing, vibration testing, and shock testing
 - Additional thermal vacuum test to demonstrate system durability and stable performance after mechanical testing

Prometheus Component and System Qualification

- Materials qualifications
 - JOYO facility in Japan for fast spectrum fuels and nuclear structure testing
 - Advanced Test Reactor (ATR) at INL and High Flux Isotope Reactor (HFIR) for thermal neutron irradiation and testing
- Component and System Qualification
 - Gas reactor had significant uncertainty early system models
 - System testing was identified as a high priority to identify a number of challenges
 - Control challenges
 - Minimization of system losses
 - Material incompatibilities
 - Plan was to begin at component level and work up to full system performance
 - Electrically heated system was planned to be used for a Thermal Test Module (TMM) for early stage thermal and an engineering model for early prototype testing



Prometheus Component and System Qualification

- Nuclear System Qualification
 - Broken into three phases
 - Benchmark tests for initial information and cross section information on critical assemblies
 - Mock-up tests to qualify design methods
 - Ground test reactor to test various operating modes and improving computational models
- Critical Facilities
 - Early in the program a lack of U.S. facilities for mockup and criticality experiments was identified as a program risk
 - Potential international facilities that were identified included
 - JOYO reactor in Japan for materials testing
 - Fast Critical Assembly (FCA) in Japan for criticality experiments
 - BOR-60 reactor in Russia for materials testing
 - PHENIX reactor in France for materials testing
 - Prototype Ground Test Reactor (GTR) facility was considered but would introduce siting and construction schedule risk
 - Lack of existing domestic critical facilities led some to push for designs to be effectively tested in non-nuclear tests

Presidential Memorandum

- Recent presidential memorandum helps to clarify the process of launching space nuclear systems
- Tier 2 approval consists of the head of the sponsoring agency for federal projects or the secretary of transportation for commercial projects and LEU
- Tier 3 approval consists of the President or Director of OSTP for approval of federal launches that use a non-LEU fission system
- Safety Analysis Report (SAR) requires
 - Launch, staging, flyby, and reentry accident scenarios that may expose the public or environment to radiological effects
 - Analysis of consequences of a maximally exposed member of the public
 - If possible, make use of previous mission reviews and experience

Presidential Memorandum Tier Descriptions

1	<100,000 times total A2 Table 2 value in IAEC SSR-6	Head of Sponsoring Agency	Secretary of Transportation
2	>100,000 times total A2 Table 2 value in IAEC SSR-6	Head of Sponsoring Agency	Secretary of Transportation
2	Tier 1 with 1:1,000,000 probability of a member of public receiving 5 to 25 rem TED	Head of Sponsoring Agency	Secretary of Transportation
2	Any launch of LEU fission systems with additional safety review	Head of Sponsoring Agency	Secretary of Transportation
3	1:1,000,000 probability of a member public receiving >25 rem TED	President or OSTP Director	Secretary of Transportation
3	Any launch of non-LEU fission system with additional safety review	President or OSTP Director	Secretary of Transportation

Future Reactor Qualification

- Prototypic non-nuclear tests and an increased number of tests can improve system reliability
- Electrically heated non-nuclear tests can help to increase system reliability
 - Quantifies component behavior
 - Identifies potentially unknown system interactions
- Materials qualification
 - Thermal or epithermal designs can use ATR or HIFR reactors
 - TREAT reactor can provide rapid power transients

Future Reactor Qualification


- Security and Transportation
 - Type of fuel used can be a significant driver in costs
 - HEU can create higher security risks and costs during manufacture and transport
- Component Testing
 - Standalone component testing is recommended prior to larger system integration
 - Characterize component performance, failure modes, and reliability
 - Reduce likelihood of system performance shortfalls
- Ground Testing
 - Using electrically heated systems and nuclear ground test is likely the most cost and schedule effective path to certify a system
 - Electrically heated units help to verify concept of operations (CONOPS), off nominal operational modes, and system lifetime
 - Nuclear tests help to verify final system configurations and provide a 'ground twin' for the launched reactor system

Future Reactor Qualification

- SAR Creation
 - Ideally would cover all potential missions
 - Cost and schedule constraints may not allow every case to be covered
 - System SAR may cover near term or highly likely cases rather than all encompassing cases
 - Is a living document that should be updated regularly
- Environmental and Safety Reviews
 - Preparation and review of space reactor environmental and safety reviews can be extrapolated from the NRC reviews for small modular reactors and isotope facilities
 - Lack of mature space reactor designs creates some uncertainty

Future Space Reactor Qualification

- NRC's licensing process of Small Modular Reactors is expected to take at least 39 months
- Space reactor is expected to take a minimum of 36 months and likely 48 months due to current lack of design fidelity



Conclusions

- Space reactor development has historically been a hardware and test intensive
- Current development paths focus more on computation analysis and non-nuclear testing
- Facility needs and availability early in program lifecycle will help to minimize development surprises
- Development of a realistic cost and schedule should identify key task including
 - Required existing fabrication and test facilities
 - Required new fabrication and test facilities
 - Safety and environmental applications
 - Component and system design
 - Launch permitting
 - Component and system ground test