

Engineering Evaluation of an Integrated Off-gas System for a UNF Processing Facility

April 2021

Amy K Welty, Nick Soelberg, Stephanie Bruffey





DISCLAIMER

This information was prepared as an account of work sponsored by an agency of the U.S. Government. Neither the U.S. Government nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness, of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. References herein to any specific commercial product, process, or service by trade name, trade mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the U.S. Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the U.S. Government or any agency thereof.

Engineering Evaluation of an Integrated Off-gas System for a UNF Processing Facility

Amy K Welty, Nick Soelberg, Stephanie Bruffey

April 2021

Idaho National Laboratory Idaho Falls, Idaho 83415

http://www.inl.gov

Prepared for the U.S. Department of Energy Under DOE Idaho Operations Office Contract DE-AC07-05ID14517

Engineering Evaluation of an Integrated Off-gas System for a UNF Processing Facility

A. K. Welty and Nick Soelberg, INL Stephanie Bruffey, ORNL

UK/US Off-Gas Technical Exchange April 19, 2021




Outline

- Scope
- Motivation
- Assumptions
- Key Findings
- Follow-on Analysis

Overarching aims of evaluation

- This analysis is an initial engineering evaluation and design of the off-gas abatement systems required for future used nuclear fuel (UNF) reprocessing facilities.
- This engineering study is conceptual and not tied to a specific UNF processing facility.
 - Intended to assess the complexity and sizes of the required systems.
- It evaluates:
 - (1) relative equipment sizes,
 - (2) energy requirements,
 - (3) key instrumentation requirements, and
 - (4) the extent to which key design data are, or are not, available for the off-gas systems.
- Only addresses the designs of the head-end off-gas (HOG), dissolver off-gas (DOG), and vessel off-gas (VOG) systems.
 - HOG and DOG systems are considered with and without tritium pretreatment.



Major Assumptions

- The basis of the facility design
 - Aqueous processing of UNF
 - Throughput = 1000 t/year
 - Plant operating time = 200 days/year.
 - Off-gas systems operate 365 days/year.
 - Fuel cooling time = 5 years
 - Fuel type = UOX (UO₂-based fuel), 60 GWd/tIHM burnup
 - Steady state conditions.
 - Halogens other than iodine from the UNF and process chemicals are included for sizing the DOG iodine beds.
 - Maximum decontamination factors (DFs):
 - ³H, ¹⁴C, ⁸⁵Kr, and ¹²⁹I are those found in Jubin et al. (2012).
 - Ruthenium DF is found in Jubin et al. (2014).

Target DFs used in analysis

Table 1. Maximum DF values for the isotopes considered in this study	
Isotope	DF
³ H	200
¹⁴ C	10
⁸⁵ Kr	50
129	3000
¹⁰⁶ Ru	3.0×10^{7}


Process design assumptions

- Tritium capture system based on two primary operating flowsheets.
 - Case 1: Base case UNF dissolution.
 - Case 2: Adds air tritium pretreatment (TPT).
 - A NO_x-based TPT, being studied because it may be more efficient, is addressed in a separate report.
- lodine capture analysis addresses iodine distribution throughout the facility and iodine speciation.
 - Silver mordenite (AgZ)
 - Silver-functionalized silica-aerogel (Ag-Aerogel) (Matyáš et al. 2011)
- Removal of NO_x is based on acid/water scrubbing.


Process design assumptions

- Caustic scrubbing is used for the removal of ¹⁴C (e.g., ¹⁴CO₂).
- Both cryogenic and sorbent-based capture systems for noble gas capture are evaluated.
- Tramp species are included.
 - Halogens (fluorine, chlorine, etc) from process chemicals.
 - Water vapor and CO₂ in the plant air.
- The effects of extended operations on equipment size and design are considered.
 - Where possible, sorbent beds are designed for greater than a 6 month operating lifetime.

Process streams considered




Aqueous head-end and DOG Base Case




Aqueous head-end and DOG with air tritium pretreatment


Aqueous Head-end and Dissolver Off-gas Systems Near-Term Target Case #1, Air Tritium Pretreatment



Vessel off-gas system




Ruthenium removal




RUTHENIUM REMOVAL DISSOLVER OFF-GAS


DOG iodine removal




Kr/Xe removal




Kr/Xe removal





Kr CAPTURE (HZ-PAN)



Kr PURIFICATION

Additional

- Energy balance and recovery were not evaluated.
- Gas and water cycle/recycle were not evaluated.
- The possibility of installing by-passes around equipment for use when there is insufficient volatile radioactive species present to warrant treatment should be investigated.
- Subsequent studies should add similar assessments for the cell off-gas (COG) and melter off-gas (MOG) systems.

Questions/Comments

