



# OVERVIEW OF RECENT PU-238 PRODUCTION ACTIVITIES AT IDAHO NATIONAL LABORATORY

April 2021

*Changing the World's Energy Future*

Andrew John Zillmer, Austen D Fradeneck, Joshua David Fishler, David F Reeder, Ryan L Marlow, Jagoda Urban-Klaehn, Michael A Reichenberger, Mark A Hill, Richard Harmon Howard, William Spencer Green, Craig R Tyler, Brian J Gross, Erik S Rosvall



#### **DISCLAIMER**

This information was prepared as an account of work sponsored by an agency of the U.S. Government. Neither the U.S. Government nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness, of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. References herein to any specific commercial product, process, or service by trade name, trade mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the U.S. Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the U.S. Government or any agency thereof.

# **OVERVIEW OF RECENT PU-238 PRODUCTION ACTIVITIES AT IDAHO NATIONAL LABORATORY**

**Andrew John Zillmer, Austen D Fradeneck, Joshua David Fishler, David F Reeder,  
Ryan L Marlow, Jagoda Urban-Klaehn, Michael A Reichenberger, Mark A Hill,  
Richard Harmon Howard, William Spencer Green, Craig R Tyler, Brian J Gross,  
Erik S Rosvall**

**April 2021**

**Idaho National Laboratory  
Idaho Falls, Idaho 83415**

**<http://www.inl.gov>**

**Prepared for the  
U.S. Department of Energy  
Under DOE Idaho Operations Office  
Contract DE-AC05-00OR22725**

# OVERVIEW OF RECENT PU-238 PRODUCTION ACTIVITIES AT IDAHO NATIONAL LABORATORY

Andrew Zillmer, William Green, Craig Tyler, Brian Gross,  
Erik Rosvall, Austen Fradeneck, Joshua Fishler, David  
Reeder, Ryan Marlow, Jagoda Urban-Klaehn, Michael  
Reichenberger, Mark Hill and Richard Howard

# Introduction

- The production of Radioisotope Power Systems (RPS) has been an ongoing endeavor for the U.S. Department of Energy (DOE) and its predecessor agencies for the past six decades.
- DOE has contracted the Idaho National Laboratory (INL) to provide RPS in support of National Aeronautics and Space Administration (NASA) missions
- INL is supporting the Department of Energy's efforts to restart Pu-238 production for use in future NASA missions that use Radioisotope Power Systems (RPS)
- Plutonium-238 Fuel Services (PFS) is a collaborative effort between Idaho National Laboratory (INL) and Oak Ridge National Laboratory (ORNL) to produce a constant rate of Pu-238 production
- INL has qualified targets originally designed for the High Flux Isotope Reactor for irradiation in the Advanced Test Reactor's (ATR) I-7 position and the South Flux Trap
- The process for qualifying targets containing Np-237 and irradiating in ATR is described in the following presentation




# Overview

- ATR Positions
- ATR Irradiation Qualification Process
  - Design
  - Neutronics
  - Thermal
  - Structural
  - ATR Critical Facility
- Operations
- Future Work


# Overview of ATR Positions

- I-7 and South Flux Trap (SFT) are currently qualified for Pu-238 production with targets that are shorter than the core
  - Targets are about half the height of ATR's core
  - Aligned at center to maximize Pu-238 yield
- I positions are in outer periphery of core
  - Thermal flux of  $1$  to  $9 \times 10^{12}$  n/cm<sup>2</sup>-s
  - Lower flux compared to other positions negatively impacts production rate
- Flux Traps are located in each cloverleaf
  - Thermal flux  $\sim 4$  to  $5 \times 10^{14}$  n/cm<sup>2</sup>-s



# Target Design and Qualification



- Existing targets designed for Oak Ridge National Laboratory's (ORNL) High Flux Isotope Reactor (HFIR) were used
- Spacers were used to align the targets in the Advanced Test Reactor (ATR) core
- Analysis and lessons learned from the qualification process will inform future target design and position qualifications






# Design Support

- Target Qualification required the design and fabrication of baskets, spacers, and specialized tools to handle and position the targets in ATR
- A Battelle Research Reactor cask was fabricated and payload licensing completed to enable shipment of irradiated targets containing Pu-238 for processing at ORNL
- Prior work on qualifying the I-7 position was leveraged for qualifying the South Flux Trap



# South Flux Trap Neutronics Qualification


- A neutronics model was created to reflect CAD models developed by the design engineer
- ATR operational parameters were assumed to estimate irradiation induced heating and reactivity changes
  - ATR operational time and power levels vary by cycle
  - Parameters biased the analysis in a more conservative (safer) manner
- MCNP was used with ORIGEN to perform neutronics analysis
- Baseline requirement of 60 day cycle was used for qualification
- ~30 grams of Pu-238 will be produced in the South Flux Trap
  - Approximately 2 times the amount produced in the I-7 position in 1/5 the time





# South Flux Trap Structural Qualification

- Structural analysis evaluated target and associated hardware stress and strain under various potential loading scenarios
  - Internal pressure within the target due to fission gas production
  - External pressures
  - External pressure differential along the length of the target
  - Pressure and skin friction drag forces from coolant flow
  - Flow induced loads and vibrations
  - Handling loading
- ASME B&PV Code used because it is a nationally accepted design and analysis approach





# Advanced Test Reactor – Critical (ATRC)

- Initial irradiation testing was performed on  $\text{NpO}_2$  sensors in the ATRC
- ATRC is a low power copy of ATR which runs at 600 W rather than 110 MW
- 20 minute run was used to benchmark analysis
- A target assembly of 7 targets was irradiated at low power in ATRC to determine reactivity worth
- Flux wires were used in ATRC to determine the flux profile



# ATRC Operations

- Targets shipped from ONRL were unloaded at INL's ATR Complex
- Target reactivity and effect on axial flux profile was measured in ATRC
- Targets from the ATRC run were reconfigured after testing to prepare for insertion into ATR
- Targets assembled under water by ATR Canal Operations
- Target assembly was inserted into the South Flux Trap
  - Verified to ensure it is properly clocked and seated into the chopped dummy in-pile tube



# Future Work

- The INL team is currently working to qualify several ATR core positions with an updated target design
  - New design will have a full length of the ATR core
  - Two targets will be stacked on top of each other to simplify Pu-238 processing at ORNL hot cells
- Currently plan on qualifying
  - North East Flux Trap (NEFT)
  - Inner A
  - H Position
  - South Flux Trap (SFT)
  - East Flux Trap (EFT)
- Qualification of multiple positions enables ATR to meet production goals for Pu-238

Column Header	Positions in Target	# of Locations in ATR
NEFT	23	1
Inner A	1	8
H Position	1	14
B Position	1	8
South Flux Trap	7	1
East Flux Trap	7	1
I Position	1 to 7	23

# Acknowledgements

This work was funded through DOE & NASA Interagency Agreement # NNH19OB05A and DOE contract DE-AC05-00OR22725.

The authors would like to thank Trevor Skeen and Kurt Lombard for their operational support; Doug Crawford for initial thermal engineering support, Joshua Peterson-Droogh for technical check support, Misti Lilo for technical management, and Nathan Manwaring for help with preparing qualifying ATRC experiments.