



Alabama A&M University Senior Project

December 2022

Changing the World's Energy Future

Chad M Macready



INL is a U.S. Department of Energy National Laboratory operated by Battelle Energy Alliance, LLC

DISCLAIMER

This information was prepared as an account of work sponsored by an agency of the U.S. Government. Neither the U.S. Government nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness, of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. References herein to any specific commercial product, process, or service by trade name, trade mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the U.S. Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the U.S. Government or any agency thereof.

Alabama A&M University Senior Project

Chad M Macready

December 2022

**Idaho National Laboratory
Idaho Falls, Idaho 83415**

<http://www.inl.gov>

**Prepared for the
U.S. Department of Energy
Under DOE Idaho Operations Office
Contract DE-AC07-05ID14517**

October 5, 2022

Chad Macready

Cognizant System Engineer
Senior Reactor Operator

Core Clamping Upgrades

Battelle Energy Alliance manages INL for the
U.S. Department of Energy's Office of Nuclear Energy




Idaho National Laboratory

Overview of System and Upgrades

Core Clamping System

- Four horizontally mounted clamping bars utilized to ensure alignment of fuel assemblies within the core.
- Each clamping bar is actuated by two push rods that operate through horizontal penetrations in the concrete shield.
- North and East clamping bars are flanged and bolted into position. (Operated to a hard stop)
- South and West clamping bars are spring loaded to ensure even, consistent force on fuel assemblies
- Currently operated using ½ inch hex/Allen socket welded to a long reach tool and socket wrench (81 inches)


TREAT Core Clamping Bars



North Face




North Face




North Face (NE Corner)



East Face



South Face




South Face (SW Corner)



SW Corner



West Face



West Face (NW Corner)



Flash Radiography Shielding



1 inch base plate

Raceway to Shielding



Current Tool



- 1/2 inch hex/allen socket welded to an 81 inch long reach tool and socket wrench



General Operation

- Sequencing
 - During UNCLAMPING the spring loaded bumpers must be pulled away first
 - During CLAMPING spring loaded bumpers must be applied last, after hard stop bumpers
- North and East Clamps
 - Clamping- Approximately 8 turns CCW to hard stop
 - Unclamping - ~8 turns clockwise to hard stop

General Operation

- South and West Clamps
 - Clamping
 - TURN the operator screws counterclockwise until the screw head just starts to move out of the outer tube (approximately 4 to 5 turns).
 - TURN operator screw counterclockwise another 4.5 turns.
 - VERIFY the operator screw head extends $\frac{3}{8}$ to $\frac{5}{8}$ in. beyond the outside tube.

General Operation

- South and West Clamps
 - Unclamping
 - TURN the operator screws clockwise until the screw head pulls in flush with the outer tube (approximately 4 to 5 turns).
 - TURN operator screw clockwise another 4.5 turns.

Project Goal and Engineering Inputs

- Provide a means to operate the core clamps remotely utilizing flexible shaft systems and hand wheels or electronic openers with push buttons
- New operators shall be capable of the required torque to operate the clamps (20 ft-lbs)
- Shall provide a means for visual verification (remote or local) of clamp position
- Should attach to existing clamps with only minor modifications
- Shall have a backup method of operating the clamps in the event of remote operator failure
- Spring loaded bumpers shall be pulled away first and applied last

Options/Road Blocks

- Limited Unistrut available that is currently mounted to the reactor
- New mounting onto the core structure is not an option.
- Cable tray/Raceway is available to run flexible shaft or wiring
- Limited space surround the reactor for mount to the floor
- Cannot obstruct hodoscope and radiography operations



Battelle Energy Alliance manages INL for the U.S. Department of Energy's Office of Nuclear Energy. INL is the nation's center for nuclear energy research and development, and also performs research in each of DOE's strategic goal areas: energy, national security, science and the environment.