



Local Power Impact Experiment Design for a New Fuel Type for use in the Advanced Test Reactor

November 2023

Changing the World's Energy Future

Erin Dubas



INL is a U.S. Department of Energy National Laboratory operated by Battelle Energy Alliance, LLC

DISCLAIMER

This information was prepared as an account of work sponsored by an agency of the U.S. Government. Neither the U.S. Government nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness, of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. References herein to any specific commercial product, process, or service by trade name, trade mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the U.S. Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the U.S. Government or any agency thereof.

Local Power Impact Experiment Design for a New Fuel Type for use in the Advanced Test Reactor

Erin Dubas

November 2023

**Idaho National Laboratory
Idaho Falls, Idaho 83415**

<http://www.inl.gov>

**Prepared for the
U.S. Department of Energy
Under DOE Idaho Operations Office
Contract DE-AC07-05ID14517**



NNSA
National Nuclear Security Administration

m3
MATERIAL MANAGEMENT
AND MINIMIZATION
CONVERT, REMOVE, DISPOSE

INL
Idaho National Laboratory

MPR



National Nuclear Security
Administration (NNSA)

Defense Nuclear
Nonproliferation (DNN)

Local Power Impact Experiment Design for Low Enriched Uranium Fuel for use in the Advanced Test Reactor

Erin Dubas, MPR Associates Inc.

ANS Winter Meeting

November 14, 2023

This work was funded in whole, or in part, by the National Nuclear Security Administration's (NNSA) Office of Material Management and Minimization (M3) through programs at the Idaho National Laboratory (INL).



This work was funded in whole, or in part, by the National Nuclear Security Administration's (NNSA) Office of Material Management and Minimization (M3) through programs at the Idaho National Laboratory (INL).

This work made use of Idaho National Laboratory's High Performance Computing systems located at the Collaborative Computing Center and supported by the Office of Nuclear Energy of the U.S. Department of Energy and the Nuclear Science User Facilities under Contract No. DE-AC07-05ID14517.



Introduction



The Department of Energy (DOE) National Nuclear Security Administration's (NNSA) Office of Material Management and Minimization (M3) mission is to convert, remove, and dispose of vulnerable nuclear material located at civilian sites worldwide.

- Research reactors and isotope production facilities are being converted to non-weapon usable nuclear material
- Need to develop and qualify new low enriched uranium (LEU) fuels for use in the research reactors currently using highly enriched uranium (HEU)
- Selected a monolithic U-Mo fuel plate design consisting of uranium-10 wt% molybdenum alloy (U-10Mo) foils clad in aluminum alloy 6061.
- Analysis, testing, and demonstration of the new fuel is required to ensure that it meets the operational safety, dimensional stability, thermal stability, performance, and other requirements for the reactors

Introduction

- Reactor physics safety evaluations for the ATR and ATRC currently use Monte Carlo for the 21st Century (MC21)
 - MC21 models of the ATR and ATRC are validated for use in neutronics analyses with HEU fuel
 - The new design for the LEU fuel element for the ATR, LOWE, is not covered by the current validation basis and requires validation
- Validation Objectives:
 - Provide rigorous basis for use of the ATR and ATRC models, approximations, and nuclear cross sections safety analyses for use with LOWE
 - Quantify uncertainties to inform margin

This work evaluates inputs to and proposes the Power Impact Validation Experiment to validate the MC21 models for predicting power and few-group neutron spectrum in the ATR with LOWE fuel elements.



Background

- Power Measurements
 - HEU fission wires are placed on a polyethylene flux wand
 - 17 wands are inserted into different channels between fuel element plates in an element (half the core is instrumented)
 - The fission wires are irradiated during a flux run, during which the reactor is brought to a critical state for 20 minutes
 - Once the cycle is done, the fission wires are taken to the INL Radiological Measurements Laboratory (RML) where the saturation fission rate for each wire is determined using beta counting
 - The beta counts are correlated to powers using HELIOS and MC21, in parallel. Lobe power is calculated from multiple fission wire power measurements.
 - Correlations were developed specifically for HEU fission wires being irradiated in an HEU environment

$$P_E = \frac{\sum (FR_{wire,i} \times Energy/Fission \times W_{n,i}) \times m_{U235E}}{N \times F}$$

P_E = Fuel element power, where:

$FR_{wire,i}$ = Fission rate in wire i

$\frac{Energy}{Fission}$ = Assumed energy per fission

$W_{n,i}$ = Weighting factor for wire i

m_{U235E} = Fuel element U235 mass

N = Normalization factor

F = Peaking factor at midplane




Figure 1. Flux Wand Set Locations [3]

14-WHT02-89-2



Approach

- Objective
 1. **Evaluate modeling accuracy for relative changes in power from the LOWE fuel element using experimental data**
 2. Correlate LEU-impacted fission rates to absolute power


Relative changes:

1. Validate the MC21 predicted fission rate values against experimental data from a flux run in the ATRC
2. Evaluate the relative impact of the LOWE element on the adjacent HEU elements


**Meeting these Objectives Gives Confidence that MC21
Captures the Flux Perturbations from the LOWE Element**

Experiment Design


- Experiment control
- Core loading



Run A




Run B

 Standard Core Loading
(Mark IV and V)


 LOWE

Experiment Design


- Experiment control
- Core loading
- Amount of instrumentation



Azimuthal Instrumentation



Axial Instrumentation






Agenda


- **Experiment Design**
 - **Define the experiment control**
 - Flux runs are expensive and take time to prepare for and run
 - **Define the core loading**
 - The ATR and ATRC use different fuel. Procuring ATR fuel for use in the ATRC would be expensive. Switching out the core loading would add multiple days to the experiment
 - **Define the level of instrumentation required**
 - How much instrumentation is needed for the experiment, and what impact will the instrumentation have on our results?

Design Considerations


- Two flux runs may be necessary for evaluating relative differences in fission rates
 - Option 1: Lobe in the same flux run as the experiment flux run [Red Circles in middle Core Loading]
 - Option 2: Separate flux run with only HEU elements [Left Core Loading]




Option 1



Option 2




Experiment Flux Run



Design Considerations



- Two flux runs are necessary to evaluate the impact of the LOWE element on power
 - Minimize outside effects
 - Minimize time and cost

Absolute Value of % Difference in Fission Wire Fission Rate		
Lobe	Average (%) ± 0.4 % Uncertainty	Maximum (%) ± 4.0 % Uncertainty
Northwest	2.2	8.8
Northeast	4.8	38.6
Center	1.6	5.6
Southwest	1.8	6.9
Southeast	2.2	5.8




Design Considerations

- Standard ATRC core loading would significantly reduce cost and schedule
 - ATRC standard loading consists of Mark IV and V elements
 - ATR standard loading consists of all Mark VII elements



Run A: Standard ATRC Loading
(Mark IV and V Elements)



Run B: Standard ATR Loading in LOWE Lobe
(Mark VII, IV and V Elements)



Design Considerations

- Standard core loading should be used
 - Difference of approximately $0.003 \Delta\$ / \Delta^\circ$
 - Standard loading is advised

Total worth is calculated as shown in Equation 8.

$$\rho_{feedback} = \frac{\left(\frac{k_2 - k_1}{k_1 * k_2} \right)}{\beta_{eff}}$$

Equation 8

Where:

$\rho_{feedback}$ = Reactivity worth (\$)

k_1, k_2 = Final k-effective for Run 1 and Run 2, respectively

β_{eff} = The delayed neutron fraction (assumed to be 0.007 per Reference 2)

Table D-5. Sensitivity to Driver Element Loading

Core Loading	Worth per Degree Change in OSCC Position, $W/\Delta P$ in (\$/°)
IV_V	0.132 ± 0.001
IV_V_LOWE	0.133 ± 0.001
VII	0.130 ± 0.001
VII_LOWE	0.131 ± 0.001

Design Considerations

- Standard core loading should be used
 - Difference of approximately 0.003 $\$/^\circ$ at most
 - LOWE element worth is appx. \$0.13 (position dependent)




Figure D-5. K-Effective vs. OSCC Position as a Function of Driver Element Loading





Figure D-6. Worth vs. Change in OSCC Position as a Function of Driver Element Loading

Design Considerations



- Evaluating the impact of fission wires on fission rate
- Quantify the effects of observation
- Negligible differences were observed

Fission Wire Bias Evaluation	
Core Loading	Max % Difference
All HEU	< 0.3%
39 HEU, 1 LOWE	< 0.3%




Summary

- Experiment Design
 - Two flux runs are necessary for evaluating relative differences in fission rates
 - Standard core loading should be used
 - There is negligible impact from the fission wires on fission rate



Azimuthal Instrumentation

Un-Instrumented
Instrumented




Axial Instrumentation


Un-Instrumented
Instrumented

Preliminary Findings

Azimuthal Output




Run A:
Standard
Loading




Run B:
LOWE in
Position 5

Axial Output



Element
4



Element
6



Preliminary Findings





References

1. Dubas, E., "Experiment Design for the Element Test-1 Local Power Impact Validation Experiment", 1129-0074-CALC-001, Revision 0.
2. Campbell, J. L., "ATR User Guide," Idaho National Laboratory, INL/EXT-64328-Rev000, September 30, 2021.
3. Brower, J. O., "Advanced Test Reactor (ATR) Conversion to Low Enriched Uranium (LEU) Fuel," INL/CON-17-42010, Idaho National Laboratory (2017).
4. Bays, S., et al., "Validating Intra-Plate Power Distributions in the Advanced Test Reactor," November 15, 2021, <https://doi.org/10.1080/00295450.2021.1980320>.
5. Hardtmayer, D., "Monte-Carlo Based Evaluation of HEU and LEU Fuel Neutron and Photon Spectra", MPR Calculation 1129-0226-CALC-007, Revision 0.